

**HYDROGEOLOGICAL  
INVESTIGATION REPORT**

**752 PETERSON ROAD**

**MUNICIPALITY OF  
HASTINGS HIGHLANDS**

**PREPARED FOR:**

**SHAHRAM RASHVAND**

**PREPARED BY:**

**C.F. CROZIER & ASSOCIATES INC.  
55 WYNDHAM STREET N, SUITE 215  
GUELPH, ON N1H 7T8**

**DECEMBER 2025**

**CFCA FILE NO. 2497-6768**

The material in this report reflects best judgment in light of the information available at the time of preparation. Any use which a third party makes of this report, or any reliance on or decisions made based on it, are the responsibilities of such third parties. C.F. Crozier & Associates Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.



<b>Revision Number</b>	<b>Date</b>	<b>Comments</b>
Rev.0	August 2024	Issued for First Submission
Rev.1	June 2025	Issued for Second Submission (DRAFT)
Rev.2	July 2025	Issued for Second Submission
Rev.3	December 2025	Issued for Third Submission

## TABLE OF CONTENTS

<b>1.0</b>	<b>Site Description.....</b>	<b>1</b>
<b>2.0</b>	<b>Physical Setting .....</b>	<b>1</b>
2.1	Physiography .....	1
2.2	Topography And Drainage .....	1
2.3	Surficial Geology .....	2
<b>3.0</b>	<b>Hydrogeology .....</b>	<b>2</b>
3.1	Mecp Well Records .....	2
<b>4.0</b>	<b>Water Supply Assessment.....</b>	<b>3</b>
4.1	Groundwater Quantity.....	3
4.2	Groundwater Quality Sampling.....	3
4.3	Impact To Nearby Well Users & Natural Features.....	4
<b>5.0</b>	<b>Nitrate Impact Assessment.....</b>	<b>5</b>
<b>6.0</b>	<b>Conclusions &amp; Summary .....</b>	<b>7</b>

## LIST OF TABLES

**Table 1:** MECP Well Records Summary  
**Table 2:** Exceedances of the Ontario Drinking Water Quality Standards

## LIST OF APPENDICES

**Appendix A:** Water Well Records  
**Appendix B:** Pumping Test Results  
**Appendix C:** Water Quality Results  
**Appendix D:** Nitrate Impact Assessment Calculations

## LIST OF FIGURES

**Figure 1:** Site Location  
**Figure 2:** Physiography  
**Figure 3:** Bedrock Geology  
**Figure 4:** Surficial Geology  
**Figure 5:** Well Records

## 1.0 Site Description

C.F. Crozier & Associates Inc. (Crozier) has been retained by Shahram Rashvand (Owner) to prepare a Hydrogeological Study in support of the proposed development located at 752 Peterson Road, in Maynooth, within the Municipality of Hastings Highlands (Figure 1). The scope of this study was designed to meet the relevant criteria of the Municipality of Hastings Highlands and other local approval agencies.

The subject lands (herein referred to as the Site) cover an area of approximately 5.19 ha and is located on the northern side of Peterson Road north of Cannon Lake, approximately 4 km west of the village of Maynooth. The majority of the site is zoned as Rural Residential (RR) with a northern portion of the site zoned as Environmental Protection (EP) per the Municipality of Hastings Highlands Zoning By-Law.

The Site currently consists of an existing garage, the foundation for the future management building and the septic system to service that building. The remainder of the property is densely forested. The property is accessed by a gravel driveway off Peterson Road. The elements envisioned for the proposed development include:

- 17 cabins with trails to a common area and parking lot.
- The common area will include a management building and pool. The common area will be serviced by a water well and septic system (both which have already been constructed).

A review of the Ministry of Environment, Conservation and Parks (MECP) Source Protection Information Atlas reveals that the Site is not located within a regulated area therefore, no specific source protection policies apply.

Please note that the following report has been revised to address the Municipality of Hastings Highlands comments addressed February 2025.

## 2.0 Physical Setting

### 2.1 Physiography

The Site is located within the physiographic region known as the Algonquin Highlands (Figure 2). The Algonquin Highlands are found in Eastern Ontario and cover an area of approximately 40,144 square kilometers. This region is characterized by hard Precambrian rock overlain by a thin layer of sandy glacial till of variable depth (Figure 3). The soils in this region are generally shallow but thickness over the bedrock varies greatly over short distances. Within the Site, there are some areas of exposed bedrock.

### 2.2 Topography and Drainage

According to the Ontario Watershed Boundaries (OWB) mapping, the Site area is situated in the Baptiste Lake - York River watershed. Surface drainage is interpreted to flow to the southeast of the Site. The topography of the site is characterised by a significant slope from the north of the property to the south towards Cannon Lake.

## 2.3 Surficial Geology

According to Ontario Geological Survey (OGS) mapping (Figure 4), the surficial geology of the Site predominantly consists of fine textured glaciolacustrine deposits comprised of silt, clay and minor sand and gravel. Pockets of modern alluvial deposits and clay to silt till are mapped within the Site boundary.

## 3.0 Hydrogeology

### 3.1 MECP Well Records

Crozier completed a review of the MECP well record database for wells within 500 m of the Site Area boundary (Figure 5). Only nine (9) wells are located within 500 m of the property, with 7433500 being mapped within the property (Appendix A). Table 1 below summarizes all the wells within 500 m.

**Table 1: MECP Well Records Summary**

Well ID	Diameter (cm)	Depth (m)	Static Level (m)	Quantity (Lpm)	Quality	Materials	Aquifer	Use	Date Completed
2907831	15.24	10.97	4.267	45.46	Fresh	Granite	BR	Domestic	06/01/1976
2908373	15.24	30.48	4.267	40.95	Fresh	Red Granite	BR	Domestic	07/13/1977
2916314	15.875	49.38	6.401	13.65	Untested	Gray/Red Granite	BR	Domestic	09/01/1994
2917532	15.875	43.28	-	31.85	Untested	Gray/Red Granite	BR	Domestic	07/29/1997
2917533	15.875	43.28	3.353	31.85	Fresh	Gray/Red Granite	BR	Domestic	07/30/1997
2921359	16.000	36.58	0.600	40	Untested	Red Granite	BR	Domestic	08/04/2006
7160138	15.875	81.44	4.084	45.5	Untested	Gray/Red Granite	BR	Domestic	11/29/2010
7388986	15.875	85.34	16.154	36.4	Untested	Gray/Red Granite	BR	Domestic	05/25/2021
7433500	15.875	59.4	6.4	30	Fresh	Gray/Red Granite	BR	Domestic	09/02/2022

Based on Table 1, the following remarks can be made:

- In general, the main material encountered in majority of the wells was gray to reddish granite bedrock.
- All nine (9) records were identified for domestic use.
- Of the nine (9) wells where pumping test were completed in, there was a maximum reported pumping rate of 45.46 litres per minute (LPM), and a minimum reported pumping rate of 13.65 LPM. The average pumping rate was 33.841 LPM.
- Static water levels range from 0.6 meters below ground surface (mbgs) to 16.154 mbgs across the Site area. The average static water level was 6 mbgs.
- Well ID 7433500 is mapped within the Site boundary. The well is a 15.85 cm diameter steel cased domestic well constructed for the site to a depth of 59.4 mbgs within granite bedrock.

The materials presented in nearby well records to the Site are consistent with OGS mapping and the soils observed onsite.

## 4.0 Water Supply Assessment

### 4.1 Groundwater Quantity

A pumping test of the existing well was completed on April 18, 2024. It should be noted that the Site is unoccupied and the domestic well has not been used with the exception of the testing completed. The pumping test was completed on well 7433500 and was pumped for 90 minutes with 50 minutes of recovery. Crozier staff measured water levels at the beginning, end and throughout the testing using a manual water level meter. Detailed testing data is provided in Appendix B.

The well was tested at a constant rate of 30 liters per minute (LPM) to evaluate the capacity of the well and its capability of producing adequate water quantity to the proposed development. After 90 minutes of pumping the water level declined from 4.60 mbgs to a pumping level of 15.70 mbgs. Following 50 minutes of recovery, the water level recovered to 8.90 mbgs, approximately 51 % of static water level. It is estimated that 95% would be achieved after an elapsed time of 197 minutes from the start of the pumping test or 107 minutes of recovery.

The well has a total available drawdown of 54.80 m based on a total depth of 59.40 m and a static water level of 4.60 m. Using a safety factor of 80% (only allowing for 80% of the total available drawdown to be utilized) the total available drawdown in the well would be 43.84 mbgs.

Extrapolating the equation to 1 year, a drawdown of approximately 33 mbgs would be seen with 1 year of continuous pumping, leaving roughly 10 m of available drawdown in the well. Crozier is of the opinion, based on the results of the pumping test and analysis, that the existing well on property is capable of producing water in at 30 LPM on a long term basis which exceeds the requirement for the development of 13.33 LPM (see Servicing Report under separate cover).

### 4.2 Groundwater Quality Sampling

Two (2) water samples were collected from the existing well during the pumping test. The first sample was collected within the first 15 minutes of pumping and the final sample was collected immediately after the pump was turned off. The samples were collected using standard sampling methods for test wells and were submitted to a third-party laboratory for analysis. Samples were analysed for the following parameters. A laboratory report is appended to this report as Appendix C.

- E.Coli and Total Coliforms
- Anions including fluoride, chloride, nitrate, nitrite, bromide, sulphate, and phosphate
- Physical tests such as conductivity, alkalinity, hardness, pH, etc.
- Ion Balance
- Total Metals

The results were compared to the Ontario Drinking Water Quality guidelines as shown in Table 2 below.

**Table 2: Exceedances of the Ontario Drinking Water Quality Standards**

Parameter	Guideline/Standard	Type	Sample 1 Beginning	Sample 2 End
Total Coliforms	Non-Detect	MAC	1	Non-Detect
Iron	0.3 mg/L	AO	0.787	0.398
Colour	5 NTU	AO	49.0	13.0
Turbidity	5 NTU	AO	7.93	2.05

OG – Operational objective; AO – Aesthetic objective; MAC – Maximum Allowable Concentration

Only one exceedance of a health-related parameter was observed in the water sample analysis – total coliforms. Total coliforms is a measure of bacteria within the sample; any detection is deemed unsuitable for consumption. The first sample was collected within 15 minutes of turning the pump on. It can be reasonably assumed that the first sample is representative of stagnant water since the bacteria was not detected after pumping for 90 minutes and the well sat unopened and unused for 2 years following installation.

Exceedances of the standards for iron, colour and turbidity were noted in the first sample as well. Similar to the above, the first sample results are interpreted to be as a result of stagnant water and not thought to be representative of aquifer quality. The objectives for iron, turbidity and colour can affect taste, look and odour of drinking water but do not impact human health. The elevated levels of iron decrease to near the guideline objective after 90 minutes of pumping and colour and turbidity decrease significantly after the first 90 minutes. It is expected that after pumping for longer periods, both would decrease to below the objective.

Although the well water meets all the health-related objectives of the Ontario Drinking Water Quality Standards, it is recommended that treatment for particulates, bacteria and the aesthetic parameters above be investigated. The intended use of the property for rentals and it is expected that water quality will be a top concern of visitors. The design of the treatment system is beyond the scope of this report, however, options for types of treatment are presented in section 5 below.

#### **4.3 Impact to Nearby Well Users & Natural Features.**

The zone of influence of a well can be estimated using the Sidchart equation:

$$R = 3000 \times H \times \sqrt{K}$$

Where **H**: is the drawdown of the well in meters.

**K**: is the hydraulic conductivity of the soil or transmissivity of the bedrock.

According to literature values for granite transmissivity in the area, transmissivity of the bedrock on the Site is estimated to range from 1 to 5 m<sup>2</sup>/day. Assuming a conservative saturated thickness of 50 m, the hydraulic conductivity of the rock is estimated to be on the order of 10<sup>-7</sup> m/s.

Given the above assumptions, it was determined that the estimated zone of influence of the existing well is approximately 100 m from the well at the maximum available drawdown of 43.84 m. There are wells located on neighbouring properties; however, they are located greater than 100 m from the well head and the well will not operate at its maximum allowable drawdown, no significant impacts to neighbouring well users or natural heritage features are anticipated.

## 5.0 Nitrate Impact Assessment

Onsite sewage systems can contribute nitrate-nitrogen to the shallow groundwater regime, which may impact drinking water quality. Therefore, the impacts of a proposed onsite sewage system must be examined to ensure that downgradient groundwater users have access to a safe and reliable drinking water supply.

The impact assessment of the proposed leaching bed has been completed in accordance with MECP Procedure D-5-4 Technical Guidelines for Individual Onsite Sewage Systems: Water Quality Impact Risk Assessment (Procedure D-5-4).

Crozier has completed a mass balance calculation to predict the concentration of nitrate-nitrogen at the property boundary using the following general assumptions, per D-5-4 Guidelines:

- The background nitrate concentration is 0.0 mg/L.
- The concentration of nitrate in the effluent is 40 mg/L, typical for conventional septic tank/leaching beds system without advanced treatment.
- The average volume of effluent generated by the proposed development is estimated to be 9,600 L/day, per the Functional Servicing & Preliminary Stormwater Management Report (Crozier, December 2025)
- The only dilution mechanism is by infiltration of surface precipitation. An infiltration value of 150 mm/year has been assigned, based on MECP Guidelines.
- 5.19 ha of the property is available for dilution purposes.

Impact assessment calculations are included in Appendix D. Using this approach, the resulting theoretical concentration of nitrate-nitrogen at the downgradient Site boundary is predicted to be 12.42 mg/L, which is above the maximum allowable concentration of nitrate-nitrogen of 10 mg/L. With 25% nitrogen removal, the nitrate concentration at the property boundary is 9.31 mg/L. Therefore, Crozier recommends that an advanced treatment unit be implemented, which may assist with further removal of nitrate-nitrogen. There are a number of CAN/BNQ certified treatment systems that can significantly reduce nitrogen in effluent, including the Waterloo Biofilter recirculating system, among others.

As outlined in the Functional Servicing & Preliminary Stormwater Management Report, an alternative scenario was considered where the total daily design sewage flow for the proposed development is 18,100 L/day (1,000 L/day per cabin). When the total daily design sewage flow for the Site is greater than 10,000 L/day, an impact assessment in accordance with Chapter 22 – Large Subsurface Disposal Systems of the MECP Design Guidelines for Sewage Works (2008) is required. Impact assessment calculations were completed in accordance with the procedure described in Chapter 22, and the target effluent concentration of nitrate-nitrogen was calculated as follows:

$$C_{effluent} = C_{max} (V_{effluent} + V_{influent})/V_{effluent}$$

Where **C<sub>effluent</sub>** is the concentration of nitrate-nitrogen required in the effluent to meet the maximum allowable concentration at the receptor.

**C<sub>max</sub>** is the maximum allowable concentration of nitrate-nitrogen at the downgradient boundary, which is 2.5 mg/L per Chapter 22.

**V<sub>influent</sub>** is the volume of infiltration based on an infiltration rate of 150 mm/m<sup>2</sup>/year over the area of the attenuation zone available for infiltration (e.g., dilution area). 5.19 ha of the property is available for dilution purposes.

**V<sub>effluent</sub>** is the average volume of treated effluent discharged to the leaching beds. As noted above the maximum daily volume to be discharged to the leaching beds is 18,100 L/day. Applying a peaking factor of 3, the average value is expected to be 6,033 L/day.

Impact assessment calculations are included in Appendix D. In this scenario, the maximum allowable concentration of nitrate-nitrogen permitted in the effluent is 11.34 mg/L. This equates to approximately 72% nitrogen removal, which is achievable by a number of CAN/BNQ certified treatment systems, including the Waterloo Biofilter WaterNOX system, etc.

Therefore, with an advanced treatment unit that includes denitrification, the proposed onsite sewage systems can meet D-5-4 and Chapter 22 requirements.

## 6.0 Conclusions & Summary

Based on the hydrogeological report above, Crozier is prepared to make the following conclusions:

- According to nearby well records and information obtained about the existing water supply well at 752 Peterson Road, it is interpreted that the groundwater supply aquifer can produce in excess of the anticipated flow rate of 13.33 LPM to service the proposed development.
- Laboratory testing of the well water in the existing water supply well revealed exceedances of the Ontario Drinking Water Quality Standards for total coliforms, iron, colour and turbidity. Only one health-related parameters were noted to be in exceedance – total coliforms. Due to the well sitting unused for two years prior to testing, the detection of coliforms in the sample is likely due to stagnant water and is not representative of aquifer conditions. Filtration systems and/or UV are commonly used to address elevated bacteria in well water.
- Exceedances of the Ontario Drinking Water Quality Standards for colour, iron and turbidity were observed in the well water sample. The objectives for these parameters are aesthetic objectives where exceedances in the guideline can negatively impact taste/smell/look of the water. Filtration and chlorination systems can reduce the total dissolved solids in water, improve colour and remove unwanted particulates.

## Recommendations

Based on the above study, Crozier is prepared to make the following recommendations regarding water quality and quantity for the proposed development

- Onsite grading should consider the well such that surface water runoff is not directed to or is able to pond around the well. Any storage of gasoline, chemicals, paints, domestic de-icing agents, and other contaminants should be contained and stored away from the wellhead.
- The well must be constructed in accordance with the Ontario Regulation 903 at a minimum and consider all local regulations. The well must be constructed upgradient from the proposed onsite sewage system and be sited following all setbacks outlined in the Ontario Building Code.
- For educational purposes on well ownership, the owner should refer to the MECP's Water Supply Wells: Requirements and the local health unit for resources. Additional resources for the owner can be accessed through the Walkerton Clean Water Centre, Green Communities Canada and the Government of Canada website.
- It is recommended that the onsite well be pumped, disinfected and tested following approval to inform the design of the water treatment system.
- The owner should follow the regulatory well maintenance requirements as outlined in the MECP's Water Supply Wells: Requirements and Best Practices. The well must be accessible for maintenance purposes permanently.

- It is recommended that the new well water be tested on roughly an annual basis for bacterial parameters. Public Health Ontario offers free well water testing for E.Coli and total coliforms bacteria through the local Health Unit. Additional water quality testing for the full suite of potable water testing parameters should occur on a biannual basis.
- Based on the water quality results obtained from the sampled well, water treatment and/or filtration is required. To address health-related parameters a UV system should be employed. It is recommended that a water treatment systems expert be consulted such that specific systems can be recommended.
- To address aesthetic and/or operational objectives, a water softener can be explored to reduce hardness, and additional filters can improve colour, pH and sodium content in water.
- It is recommended that the future owner consult the Province of Ontario's "SepticSmart" document and the Ontario Onsite Wastewater Association's "A Homeowner's Guide to a Healthy Sewage (Septic) System" for educational purposes. The Municipality of Hastings Highlands may also provide a number of resources for homeowners on maintenance and care of their septic systems.

Respectfully submitted,

**C.F. CROZIER & ASSOCIATES INC.**



Chris Gerrits, M.Sc., P.Eng.  
Director, Land Development

J:\2400\2497 - Shahram Rashvand\6768 - 752-8 Peterson Road\Reports\Hydrogeology\2025.12.15\_(2497-6768)\_752-8 Peterson Road Hydrogeology Report\_3rd Sub\_Final.docx

# APPENDIX A

## Water Well Records





Ontario

MINISTRY OF THE ENVIRONMENT  
The Ontario Water Resources Act

31 F/4

## WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED  
2. CHECK  CORRECT BOX WHERE APPLICABLE

11

2908373

MUNICIP.

29008

CON.

CON

16

COUNTY OR DISTRICT

TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE

CON., BLOCK, TRACT, SURVEY, ETC.

LOT 25-27

21+

16

008

M 10 12 17 18

24

25

47

ELEVATION

5

26

44-53

RC.

1300

30

44-53

BASIN CODE

6 26

31

44-53

DATE COMPLETED

13 07 17

13

44-53

DAY

MO

YR

44-53

17

17

17

44-53

18

17

17

44-53

19

17

17

44-53

20

17

17

44-53

21

17

17

44-53

22

17

17

44-53

23

17

17

44-53

24

17

17

44-53

25

17

17

44-53

26

17

17

44-53

27

17

17

44-53

28

17

17

44-53

29

17

17

44-53

30

17

17

44-53

31

17

17

44-53

32

17

17

44-53

33

17

17

44-53

34

17

17

44-53

35

17

17

44-53

36

17

17

44-53

37

17

17

44-53

38

17

17

44-53

39

17

17

44-53

40

17

17

44-53

41

17

17

44-53

42

17

17

44-53

43

17

17

44-53

44

17

17

44-53

45

17

17

44-53

46

17

17

44-53

47

17

17

44-53

48

17

17

44-53

49

17

17

44-53

50

17

17

44-53

51

17

17

44-53

52

17

17

44-53

53

17

17

44-53

54

17

17

44-53

55

17

17

44-53

56

17

17

44-53

57

17

17

44-53

58

17

17

44-53

59

17

17

44-53

60

17

17

44-53

61

17

17

44-53

62

17

17

44-53

63

17

17

44-53

64

17

17

44-53

65

17

17

44-53

66

17

17

44-53

67

17

17

44-53

68

17

17

44-53

69

17

17

44-53

70

17

17

44-53

71

17

17

44-53

72

17

17

44-53

73

17

17

44-53

74

17

17

44-53

75

17

17

44-53

76

17

17

44-53

77

17

17

44-53

78

17

17

44-53

79

17

17

44-53

80

17

17

44-53

81

17

17

44-53

82

17

17

44-53

83

17

17

44-53

84

17

17

44-53

85

17

17

44-53

86

17





Print only in spaces provided.  
Mark correct box with a checkmark, where applicable.

2917533





### Municipality

Con.

29008

ICON

161

County or District  	Township/Borough/City/Town/Village  <b>HERSCHEL</b>	Con block  <b>16</b>	tract survey, etc.  <b>8</b>	Lot  <b>25-27</b>				
Address  <b>P.O. Box 175 MAYNOOTH ON.</b>		Date completed  <b>30</b>	day  <b>44-53</b>	month  <b>7 97</b>				
		RC  <input type="checkbox"/>	Elevation  <input type="checkbox"/>	RC  <input type="checkbox"/>	Basin Code  <input type="checkbox"/>	ii  <input type="checkbox"/>	iii  <input type="checkbox"/>	iv  <input type="checkbox"/>
21  	T  	M  	10  	12  	14  	16  	18  	

**LOG OF OVERTURBIDEN AND BEDROCK MATERIALS (see instructions)**

31	10	14	15	21	32	43	54	65	75	80	
32											
41	WATER RECORD										
Water found at - feet	Kind of water										
85	1 <input type="checkbox"/> Fresh	3 <input type="checkbox"/> Sulphur	14	2 <input type="checkbox"/> Salty	Minerals						
swge	1 <input type="checkbox"/> Fresh	3 <input type="checkbox"/> Sulphur	19	2 <input type="checkbox"/> Salty	4 <input type="checkbox"/> Minerals	5 <input type="checkbox"/> Gas	6 <input type="checkbox"/> Plastic	7 <input type="checkbox"/> Open hole	8 <input type="checkbox"/> Concrete	9 <input type="checkbox"/> Galvanized	
20-23	1 <input type="checkbox"/> Fresh	3 <input type="checkbox"/> Sulphur	24	2 <input type="checkbox"/> Salty	4 <input type="checkbox"/> Minerals	5 <input type="checkbox"/> Gas	6 <input type="checkbox"/> Plastic	7 <input type="checkbox"/> Open hole	8 <input type="checkbox"/> Concrete	9 <input type="checkbox"/> Galvanized	
25-28	1 <input type="checkbox"/> Fresh	3 <input type="checkbox"/> Sulphur	29	2 <input type="checkbox"/> Salty	4 <input type="checkbox"/> Minerals	5 <input type="checkbox"/> Gas	6 <input type="checkbox"/> Plastic	7 <input type="checkbox"/> Open hole	8 <input type="checkbox"/> Concrete	9 <input type="checkbox"/> Galvanized	
30-33	1 <input type="checkbox"/> Fresh	3 <input type="checkbox"/> Sulphur	34	2 <input type="checkbox"/> Salty	4 <input type="checkbox"/> Minerals	5 <input type="checkbox"/> Gas	6 <input type="checkbox"/> Plastic	7 <input type="checkbox"/> Open hole	8 <input type="checkbox"/> Concrete	9 <input type="checkbox"/> Galvanized	
			60								
51	CASING & OPEN HOLE RECORD										
Inside diam inches	Material	Wall thickness inches	Depth - feet								
			From	To							
10-11	1 <input checked="" type="checkbox"/> Steel	12	-188		13-16						
6 1/4	2 <input type="checkbox"/> Galvanized		50	+2	42						
17-18	1 <input type="checkbox"/> Steel	19			20-23						
6	2 <input type="checkbox"/> Galvanized				42	142					
24-25	1 <input type="checkbox"/> Steel	26				27-30					
	2 <input type="checkbox"/> Galvanized										
	3 <input type="checkbox"/> Concrete										
	4 <input checked="" type="checkbox"/> Open hole										
	5 <input type="checkbox"/> Plastic										
SCREEN	Sizes of opening (Slot No.)			31-33	Diameter	34-36	Length	35-40			
					inches		feet				
	Material and type			Depth at top of screen			30				
				41-44			feet				
61	PLUGGING & SEALING RECORD										
	Annular space					Abandonment					
Depth set at - feet	Material and type (Cement grout, bentonite, etc.)										
From	To										
10-13	14-17										
0 20	Portland.										
18-21	22-25										
20 42	Bentonite										
26-29	30-33										
60	80										

71	Pumping test method <b>AIR</b>		Pumping rate	11-14	Duration of pumping	
	<input type="checkbox"/> Pump	<input type="checkbox"/> Baifer	<b>7</b>	GPM	15-16 Hours ..... 17-18 Mins	
	Static level	Water level end of pumping	25 Water levels during		<input type="checkbox"/> Pumping <b>7</b> <input checked="" type="checkbox"/> Recovery	
	11 19-21 feet	142 22-24 feet	15 minutes 71 26-28 feet	30 minutes 29 29-31 feet	45 minutes 17 32-34 feet	60 minutes 13 35-37 feet
If flowing give rate		38-41 GPM	Pump intake set at		Water at end of test	
		<b>AIR 142</b>	feet	<input checked="" type="checkbox"/> Clear		<input type="checkbox"/> Cloudy
Recommended pump type			Recommended pump setting	43-45	Recommended pump rate	46-49
<input type="checkbox"/> Shallow <b>Deep</b>			<b>130</b>	feet	<b>7</b>	GPM
50-53						

**LOCATION OF WELL**

In diagram below show distances of well from road and lot line. Indicate north by arrow.

A hand-drawn map showing Peterson Rd as a horizontal line. A vertical line labeled 'CANNON LAKE' is to the left. A diagonal line labeled 'MAYBROOK' extends from the end of Peterson Rd. A double-headed arrow between Peterson Rd and the diagonal line is labeled '3 3/10 km'. To the left of Peterson Rd, there are four vertical tick marks with labels: '↑ 6cm', '↓ 6cm', '↓ 4cm', and '↑ 4cm'. The label 'Hwy 62' is written below the Maybrook line.

175453

Name of Well Contractor <b>EARL V. MARQUARDT &amp; SON INC</b>	Well Contractor's Licence No. <b>3611</b>
Address <b>RR 1 Box 86 PALMER RAPIDS ON K0J-2E0</b>	
Name of Well Technician <b>DON HANNAH</b>	Well Technician's Licence No. <b>2356</b>
Signature of Technician/Contractor <i>Earl V. Marquardt &amp; Son Inc.</i>	Submission date <b>4 8 97</b>

MINISTRY USE ONLY	Data source	58	Contractor	59-62	Date received	63-68	80
			<b>3611</b>		<b>AUG 14 1997</b>		
Date of inspection		Inspector					
Remarks							

## Instructions for Completing Form

- For use in the Province of Ontario only. This document is a permanent **legal** document. Please retain for future reference.
- All Sections **must** be completed in full to avoid delays in processing. Further instructions and explanations are available on the back of this form.
- Questions regarding completing this application can be directed to the Water Well Management Coordinator at 416-235-6203.
- All metre measurements shall be reported to 1/10<sup>th</sup> of a metre.**
- Please print clearly in blue or black ink only.

## Well Owner's Information and Location of Well Information

MUN \_\_\_\_\_ CON \_\_\_\_\_ LOT \_\_\_\_\_

## Ministry Use Only

<b>HASTINGS</b>		<b>HERSHEL</b>		8	16
RR#/Street Number/Name <b>715 Peterson Rd</b>		City/Town/Village		Site/Compartment/Block/Tract etc.	
GPS Reading 8 3	NAD Zone 18	Easting 266069	Northing 5011416	Unit Make/Model <b>Magellan Sportrac</b>	Mode of Operation: <input type="checkbox"/> Undifferentiated <input checked="" type="checkbox"/> Averaged <input type="checkbox"/> Differentiated, specify _____

## Log of Overburden and Bedrock Materials (see instructions)

General Colour	Most common material	Other Materials	General Description	Depth From	Metres To
BROWN	SAND	GRAVEL	FIRM	0-16	0 4.9
GREY	GRANITE		MEDIUM	16-65	4.9 19.8
Light GREY	"		"	65-70	19.8 21.3
RED	"		"	70-79	21.3 24.1
GREY	"		"	79-105	24.1 32.0
RED	"		"	105-120	32.0 36.6

AIR TEST 60 gpm

Hole Diameter		
Depth	Metres	Diameter
From	To	Centimetres

Construction Record				
Inside diam centimetres	Material	Wall thickness centimetres	Depth	Metres
			From	To
<b>Casing</b>				
16	<input checked="" type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized		0.48	+0.6 6.2
	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized			
	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized			
<b>Screen</b>				
Outside diam	<input type="checkbox"/> Steel <input type="checkbox"/> Fibreglass <input type="checkbox"/> Plastic <input type="checkbox"/> Concrete <input type="checkbox"/> Galvanized	Slot No.		
<b>No Casing or Screen</b>				
15.4	Open hole		6.2	36.6

Test of Well Yield		
Pumping test method	Draw Down	Recovery
<b>PUMP</b>	Draw Down Time min Water Level Metres	Recovery Time min Water Level Metres
Pump intake set at - (metres) 30	Static Level 0.6	3.07
Pumping rate - (litres/min) 40	1 0.9	2.99
Duration of pumping 1 hrs + min	2 1.0	2.99
Final water level end of pumping 3 metres	3 1.08	2.93
Recommended pump type. Shallow <input checked="" type="checkbox"/> Deep	4 1.16	2.88
Recommended pump depth. 10 metres	5 1.24	2.78
Recommended pump rate. 40 (litres/min)	10 1.55	2.61
If flowing give rate - (litres/min)	15 1.84	2.46
If pumping discontinued, give reason.	20 2.03	2.36
	25 2.22	2.3
	30 2.4	2.27
	40 2.73	2.24
	50 3.0	2.21
	60 3.23	2.19

## Water Record

Water found at Metres / Kind of Water

32 m  Fresh  Sulphur  
 Gas  Salty  Minerals  
 Other: \_\_\_\_\_

..... m  Fresh  Sulphur  
 Gas  Salty  Minerals  
 Other: \_\_\_\_\_

..... m  Fresh  Sulphur  
 Gas  Salty  Minerals  
 Other: \_\_\_\_\_

After test of well yield, water was

 Clear and sediment free Other, specify \_\_\_\_\_Chlorinated  Yes  No

Plugging and Sealing Record		<input checked="" type="checkbox"/> Annular space <input type="checkbox"/> Abandonment
Depth set at - Metres	Material and type (bentonite slurry, neat cement slurry) etc.	Volume Placed (cubic metres)
From	To	
0	Bentonite Slurry	1/3

## Method of Construction

Cable Tool  Rotary (air)  Diamond  Digging  
 Rotary (conventional)  Air percussion  Jetting  Other  
 Rotary (reverse)  Boring  Driving

## Water Use

Domestic  Industrial  Public Supply  Other  
 Stock  Commercial  Not used \_\_\_\_\_  
 Irrigation  Municipal  Cooling & air conditioning

## Final Status of Well

Water Supply  Recharge well  Unfinished  Abandoned, (Other)  
 Observation well  Abandoned, insufficient supply  Dewatering \_\_\_\_\_  
 Test Hole  Abandoned, poor quality  Replacement well

## Well Contractor/Technician Information

Name of Well Contractor

EARL V. MARQUARDT &amp; SONS INC

Well Contractor's Licence No.

3611

Business Address (street name, number, city etc.)

RR1 Box 86 PALMER RAPIDS ON K0J-2E0

Name of Well Technician (last name, first name)

MARQUARDT TERRY

Well Technician's Licence No.


762

Signature of Technician/Contractor

X Terry Marquardt

Date Submitted

2006



Audit No. **z 42061** Date Well Completed **06 08 09**  
 Was the well owner's information package delivered?  Yes  No Date Delivered **06 08 09**

Ministry Use Only		
Data Source	Contractor	
	<b>3611</b>	
Date Received <b>SEP 19 2006</b>	MM DD	Date of Inspection YYYY MM DD
Remarks		Well Record Number



## Well Owner's Information

First Name	Last Name / Organization Elite Property Group	E-mail Address projects@elitepropertygroup.org	<input type="checkbox"/> Well Constructed by Well Owner
Mailing Address (Street Number/Name) 862 Upper Canada Drive		Municipality Sarnia	Province ON
		Postal Code N 7 T 1 A 4	Telephone No. (Inc. area code) 5 1 9 3 8 3 3 0 6 3

## Well Location

Address of Well Location (Street Number/Name) (No Civic) Peterson Road		Township Hastings Highlands	Lot 9	Concession 16
County/District/Municipality Hastings		City/Town/Village		Province Ontario
UTM Coordinates NAD 83	Zone 1 8	Easting 2 6 5 6 3 5	Northing 5 0 1 1 1 3 0	Municipal Plan and Sublot Number Other

## Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
brown	sand - gravel mix			0'	8'
dark grey	granite			8'	42'
red / grey	granite mix		bad broken seam 270' - 275'	42'	280'

## Annular Space

Depth Set at (m/ft) From	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0'	20' cement slurry	5 bags

## Method of Construction

## Well Use

<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Diamond	<input type="checkbox"/> Public	<input type="checkbox"/> Commercial	<input type="checkbox"/> Not used
<input checked="" type="checkbox"/> Rotary (Conventional)	<input type="checkbox"/> Jetting	<input type="checkbox"/> Domestic	<input type="checkbox"/> Municipal	<input type="checkbox"/> Dewatering
<input type="checkbox"/> Rotary (Reverse)	<input type="checkbox"/> Driving	<input type="checkbox"/> Livestock	<input type="checkbox"/> Test Hole	<input type="checkbox"/> Monitoring
<input type="checkbox"/> Boring	<input type="checkbox"/> Digging	<input type="checkbox"/> Irrigation	<input type="checkbox"/> Cooling & Air Conditioning	
<input type="checkbox"/> Air percussion		<input type="checkbox"/> Industrial		
<input type="checkbox"/> Other, specify		<input type="checkbox"/> Other, specify		

## Construction Record - Casing

## Status of Well

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft)	From	To	<input checked="" type="checkbox"/> Water Supply
6 1/4"	steel	.188"	+ 2'	20'		<input type="checkbox"/> Replacement Well
						<input type="checkbox"/> Test Hole
						<input type="checkbox"/> Recharge Well
						<input type="checkbox"/> Dewatering Well
						<input type="checkbox"/> Observation and/or Monitoring Hole
						<input type="checkbox"/> Alteration (Construction)
						<input type="checkbox"/> Abandoned, Insufficient Supply
						<input type="checkbox"/> Abandoned, Poor Water Quality
						<input type="checkbox"/> Abandoned, other, specify
						<input type="checkbox"/> Other, specify

## Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft)	From	To

## Water Details

## Hole Diameter

Water found at Depth 270' (m/ft)	Kind of Water: <input type="checkbox"/> Fresh <input type="checkbox"/> Untested <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify	Depth (m/ft)	Diameter (cm/in)
Water found at Depth 275' (m/ft)	Kind of Water: <input type="checkbox"/> Fresh <input type="checkbox"/> Untested <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify	From 0'	To 20'
Water found at Depth (m/ft)	Kind of Water: <input type="checkbox"/> Fresh <input type="checkbox"/> Untested <input type="checkbox"/> Gas <input type="checkbox"/> Other, specify	20'	6"

## Well Contractor and Well Technician Information

Business Name of Well Contractor Bernard Marquardt & Son Ltd.	Well Contractor's Licence No. 3 6 5 1
Business Address (Street Number/Name) 8 Crescent Drive, RR# 1	Municipality Palmer Rapids

Province ON	Postal Code K 0 J 2 E 0	Business E-mail Address info@cleandrinkingwater.ca
Bus. Telephone No. (Inc. area code) 6 1 3 7 5 8 2 2 3 8	Name of Well Technician (Last Name, First Name) Marquardt, Brad	
Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted 2 0 2 1 0 5 2 5

## Results of Well Yield Testing

Draw Down Time (min)	Water Level (m/ft)	Recovery Time (min)	Water Level (m/ft)
Static Level 1	53'		
1	56' 2"	1	122'
2	59' 6"	2	117' 3"
3	63'	3	113'
4	65' 5"	4	108' 2"
5	69'	5	104' 3"
10	77' 7"	10	97' 9"
15	83'	15	91'
20	90'	20	85'
25	95' 9"	25	80'
30	99' 7"	30	76' 2"
40	109' 2"	40	69' 1"
50	120' 3"	50	60'
60	128' 4"	60	54' 9"

## Map of Well Location

Please provide a map below following instructions on the back.

Comments:  
Distance from Property Line 375'  
Distance from road 190'

Well owner's information package delivered <input type="checkbox"/> Yes <input type="checkbox"/> No	Date Package Delivered Y Y Y M M D D	Ministry Use Only Audit No. Z338976
	Date Work Completed 2 0 2 1 0 5 2 5	JUN 06 2021



## Map: Well records

This map allows you to search and view well record information from reported wells in Ontario.

Full dataset is available in the Open Data catalogue (<https://data.ontario.ca/dataset/well-records>).

---

[Go Back to Map](#)

### Well ID

Well ID Number: 7433500

Well Audit Number: Z389992

Well Tag Number: A354294

*This table contains information from the original well record and any subsequent updates.*

### Well Location

<b>Address of Well Location</b>	
<b>Township</b>	HERSCHEL TOWNSHIP
<b>Lot</b>	009
<b>Concession</b>	CON 16
<b>County/District/Municipality</b>	HASTINGS
<b>City/Town/Village</b>	
<b>Province</b>	ON

Postal Code	n/a
UTM Coordinates	NAD83 — Zone 18 Easting: 265875.00 Northing: 5011356.00
Municipal Plan and Sublot Number	
Other	

## Overburden and Bedrock Materials Interval

General Colour	Most Common Material	Other Materials	General Description	Dept h From	Dept h To

## Annular Space/Abandonment Sealing Record

Depth From	Depth To	Type of Sealant Used (Material and Type)	Volume Placed	

## Method of Construction & Well Use

Method of Construction	Well Use	

## Status of Well

### Construction Record - Casing

Inside Diameter	Open Hole or material	Depth From	Depth To	

## Construction Record - Screen

Outside Diameter	Material	Depth From	Depth To	

## Well Contractor and Well Technician Information

Well Contractor's Licence Number: 7900

## Results of Well Yield Testing

After test of well yield, water was	
If pumping discontinued, give reason	
Pump intake set at	
Pumping Rate	
Duration of Pumping	
Final water level	
If flowing give rate	
Recommended pump depth	

Recommended pump rate	
Well Production	
Disinfected?	

## Draw Down & Recovery

Draw Down Time(min)	Draw Down Water level	Recovery Time(min)	Recovery Water level
SWL			
1		1	
2		2	
3		3	
4		4	
5		5	
10		10	
15		15	
20		20	
25		25	
30		30	
40		40	
45		45	
50		50	

60		60	

## Water Details

Water Found at Depth	Kind

## Hole Diameter

Depth From	Depth To	Diameter

**Audit Number:** Z389992

**Date Well Completed:** September 02, 2022

**Date Well Record Received by MOE:** November 07, 2022

### Related

How to use a Ministry of the Environment map (<https://www.ontario.ca/page/how-use-ministry-environment-map#wells>)

Technical documentation: Metadata record (<https://data.ontario.ca/dataset/well-records/resource/3031344e-e3f2-48d5-888c-c1deadfd2f77>)

# APPENDIX B

## Pumping Test Results




Project:	752 Peterson Road	Created By:	VM
Project No.:	2497-6768	Checked By:	
Well ID:	7433599		
Date:	2024-04-18		


SWL	4.60		Total Available Drawdown	1	54.80		Depth of Well	1	59.40
T/Screen	59.40			1000000	54.80			1000000	59.40
Pump intake			80% Available Drawdown	1	43.84				
Avail. DD	54.80			1000000	43.84				
	8 IGPM	0.50 L/s							
Time	DD (ft)	WL (m)	REC (ft)	WL (m)					
0	4.60								
1	6.52								
2	7.34								
3	7.90								
4	8.31								
5	8.65								
10	9.76								
15	10.50								
20	11.11								
25	11.65								
30	12.12								
35	12.69								
40	12.96								
45	13.37								
50	13.76								
55	14.31								
60	14.34								
65	14.56								
70	14.81								
80	15.30								
90	15.70		15.70						
91			13.73						
92			12.68						
93			12.17						
94			11.82						
95			11.60						
100			10.98						
105			10.58						
130			9.32						
140			8.90						
	LPM	0.50							
	DD	11.10							
	Total DD%	20.26							
	SC (L/s/m)	0.0450							
	Inc. DD%								
	Inc. L/s %								

### 752-8 Peterson Road, Maynooth


0.50 L/s    80% Available Drawdown    Total Available Drawdown    Depth of Well



## 752-8 Peterson Road, Maynooth



## 752-8 Peterson Road, Maynooth



# APPENDIX C

## Water Quality Results

## CERTIFICATE OF ANALYSIS

**Work Order**: **WT2409348****Client**: **CF Crozier & Associates****Contact**

: Josie Gerrits

**Address**: 2800 High Point Drive  
Milton ON Canada L9T 6P4**Telephone**

: ----

**Project**

: 2457-6768

**PO**

: ----

**C-O-C number**

: ----

**Sampler**

: ----

**Site**

: ----

**Quote number**

: 2024 SOA

**No. of samples received**

: 2

**No. of samples analysed**

: 2

**Page**

: 1 of 5

**Laboratory**

: ALS Environmental - Waterloo

**Account Manager**

: Andrew Martin

**Address**: 60 Northland Road, Unit 1  
Waterloo ON Canada N2V 2B8**Telephone**

: +1 519 886 6910

**Date Samples Received**

: 19-Apr-2024 14:00

**Date Analysis Commenced**

: 20-Apr-2024

**Issue Date**

: 27-Apr-2024 16:12

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QC Interpretive report to assist with Quality Review and Sample Receipt Notification (SRN).

### **Signatories**

This document has been electronically signed by the authorized signatories below. Electronic signing is conducted in accordance with US FDA 21 CFR Part 11.

<b>Signatories</b>	<b>Position</b>	<b>Laboratory Department</b>
John Tang	Lab Analyst	Inorganics, Waterloo, Ontario
Jon Fisher	Production Manager, Environmental	Inorganics, Waterloo, Ontario
Kelly Fischer	Technical Specialist	Inorganics, Waterloo, Ontario
Kelly Fischer	Technical Specialist	Metals, Waterloo, Ontario
Nik Perkio	Inorganics Analyst	Inorganics, Waterloo, Ontario
Nik Perkio	Inorganics Analyst	Metals, Waterloo, Ontario
Zeba Patel	Analyst	Microbiology, Waterloo, Ontario

## General Comments

The analytical methods used by ALS are developed using internationally recognized reference methods (where available), such as those published by US EPA, APHA Standard Methods, ASTM, ISO, Environment Canada, BC MOE, and Ontario MOE. Refer to the ALS Quality Control Interpretive report (QCI) for applicable references and methodology summaries. Reference methods may incorporate modifications to improve performance.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

Please refer to Quality Control Interpretive report (QCI) for information regarding Holding Time compliance.

Key : CAS Number: Chemical Abstracts Services number is a unique identifier assigned to discrete substances  
LOR: Limit of Reporting (detection limit).

Unit	Description
-	no units
%	percent
µS/cm	microsiemens per centimetre
CFU/100mL	colony forming units per hundred millilitres
CU	colour units (1 cu = 1 mg/l pt)
meq/L	milliequivalents per litre
mg/L	milligrams per litre
NTU	nephelometric turbidity units
pH units	pH units

<: less than.

>: greater than.

Surrogate: An analyte that is similar in behavior to target analyte(s), but that does not occur naturally in environmental samples. For applicable tests, surrogates are added to samples prior to analysis as a check on recovery.

Test results reported relate only to the samples as received by the laboratory.

UNLESS OTHERWISE STATED on SRN or QCI Report, ALL SAMPLES WERE RECEIVED IN ACCEPTABLE CONDITION.

## Workorder Comments

<1 or Not Detected with LOR of 1 equals Zero (0).

Not Detected = Absent; Detected = Present.

## Qualifiers

Qualifier	Description
DLDS	<i>Detection Limit Raised: Dilution required due to high Dissolved Solids / Electrical Conductivity.</i>



## Analytical Results

Sub-Matrix: Drinking Water

(Matrix: Water)

Client sample ID					Sample 1	Sample 2	---	---	---
Client sampling date / time					18-Apr-2024 12:00	18-Apr-2024 13:15	---	---	---
Analyte	CAS Number	Method/Lab	LOR	Unit	WT2409348-001	WT2409348-002	-----	-----	-----
					Result	Result	---	---	---
<b>Physical Tests</b>									
Alkalinity, bicarbonate (as HCO <sub>3</sub> )	71-52-3	E290/WT	1.0	mg/L	106	106	---	---	---
Alkalinity, carbonate (as CO <sub>3</sub> )	3812-32-6	E290/WT	1.0	mg/L	<1.0	<1.0	---	---	---
Alkalinity, hydroxide (as OH)	14280-30-9	E290/WT	1.0	mg/L	<1.0	<1.0	---	---	---
Alkalinity, total (as CaCO <sub>3</sub> )	---	E290/WT	1.0	mg/L	87.1	86.8	---	---	---
Colour, apparent	---	E330/WT	2.0	CU	49.0	13.0	---	---	---
Conductivity	---	E100/WT	1.0	µS/cm	185	181	---	---	---
Hardness (as CaCO <sub>3</sub> ), from total Ca/Mg	---	EC100A/WT	0.50	mg/L	82.1	82.6	---	---	---
pH	---	E108/WT	0.10	pH units	8.16	8.21	---	---	---
Solids, total dissolved [TDS]	---	E162/WT	10	mg/L	111 <small>DLDS</small>	120 <small>DLDS</small>	---	---	---
Solids, total dissolved [TDS], calculated	---	EC103A/WT	1.0	mg/L	120	118	---	---	---
Turbidity	---	E121/WT	0.10	NTU	7.93	2.05	---	---	---
Langelier index (@ 20°C)	---	EC105A/WT	0.010	-	0.147	0.190	---	---	---
Langelier index (@ 4°C)	---	EC105A/WT	0.010	-	-0.102	-0.057	---	---	---
pH, saturation (@ 20°C)	---	EC105A/WT	0.010	pH units	8.01	8.02	---	---	---
pH, saturation (@ 4°C)	---	EC105A/WT	0.010	pH units	8.26	8.27	---	---	---
<b>Anions and Nutrients</b>									
Ammonia, total (as N)	7664-41-7	E298/WT	0.0050	mg/L	<0.0050	0.0059	---	---	---
Bromide	24959-67-9	E235.Br/WT	0.10	mg/L	<0.10	<0.10	---	---	---
Chloride	16887-00-6	E235.Cl/WT	0.50	mg/L	0.54	0.55	---	---	---
Fluoride	16984-48-8	E235.F/WT	0.020	mg/L	0.118	0.117	---	---	---
Nitrate (as N)	14797-55-8	E235.NO3/WT	0.020	mg/L	0.024	0.026	---	---	---
Nitrate + Nitrite (as N)	---	EC235.N+N/WT	0.0032	mg/L	0.0240	0.0260	---	---	---
Nitrite (as N)	14797-65-0	E235.NO2/WT	0.010	mg/L	<0.010	<0.010	---	---	---
Phosphate, ortho-, dissolved (as P)	14265-44-2	E378-U/WT	0.0010	mg/L	<0.0010	<0.0010	---	---	---
Sulfate (as SO <sub>4</sub> )	14808-79-8	E235.SO4/WT	0.30	mg/L	9.13	8.93	---	---	---
<b>Microbiological Tests</b>									
Coliforms, Escherichia coli [E. coli]	---	E012A.EC/WT	1	CFU/100mL	Not Detected	Not Detected	---	---	---
Coliforms, total	---	E012.TC/WT	1	CFU/100mL	1	Not Detected	---	---	---



## Analytical Results

Sub-Matrix: Drinking Water

(Matrix: Water)

Analyte	CAS Number	Method/Lab	LOR	Unit	Client sample ID	Sample 1	Sample 2	---	---	---
					Client sampling date / time	18-Apr-2024 12:00	18-Apr-2024 13:15	---	---	---
					Result	WT2409348-001	WT2409348-002	-----	-----	-----
<b>Microbiological Tests</b>										
coliforms, total background	---	E012.BG.TC/ WT	1	CFU/100mL	4	3	---	---	---	---
<b>Metals</b>										
Sodium adsorption ratio [SAR]	---	EC102/WT	0.10	-	0.14	0.14	---	---	---	---
<b>Ion Balance</b>										
Anion sum	---	EC101A/WT	0.10	meq/L	1.95	1.94	---	---	---	---
Cation sum (total)	---	EC101A/WT	0.10	meq/L	1.89	1.88	---	---	---	---
Ion balance (APHA)	---	EC101A/WT	0.010	%	-1.56	-1.57	---	---	---	---
Ion balance (cations/anions)	---	EC101A/WT	0.01	%	96.9	96.9	---	---	---	---
<b>Total Metals</b>										
Aluminum, total	7429-90-5	E420/WT	0.0030	mg/L	0.0082	0.0080	---	---	---	---
Antimony, total	7440-36-0	E420/WT	0.00010	mg/L	<0.00010	<0.00010	---	---	---	---
Arsenic, total	7440-38-2	E420/WT	0.00010	mg/L	<0.00010	<0.00010	---	---	---	---
Barium, total	7440-39-3	E420/WT	0.00010	mg/L	0.0391	0.0403	---	---	---	---
Beryllium, total	7440-41-7	E420/WT	0.000020	mg/L	<0.000020	<0.000020	---	---	---	---
Bismuth, total	7440-69-9	E420/WT	0.000050	mg/L	<0.000050	<0.000050	---	---	---	---
Boron, total	7440-42-8	E420/WT	0.010	mg/L	<0.010	<0.010	---	---	---	---
Cadmium, total	7440-43-9	E420/WT	0.0000050	mg/L	<0.0000050	<0.0000050	---	---	---	---
Calcium, total	7440-70-2	E420/WT	0.050	mg/L	25.3	25.3	---	---	---	---
Cesium, total	7440-46-2	E420/WT	0.000010	mg/L	<0.000010	<0.000010	---	---	---	---
Chromium, total	7440-47-3	E420/WT	0.00050	mg/L	<0.00050	<0.00050	---	---	---	---
Cobalt, total	7440-48-4	E420/WT	0.00010	mg/L	<0.00010	<0.00010	---	---	---	---
Copper, total	7440-50-8	E420/WT	0.00050	mg/L	0.00104	0.00071	---	---	---	---
Iron, total	7439-89-6	E420/WT	0.010	mg/L	0.787	0.398	---	---	---	---
Lead, total	7439-92-1	E420/WT	0.000050	mg/L	<0.000050	<0.000050	---	---	---	---
Lithium, total	7439-93-2	E420/WT	0.0010	mg/L	0.0014	0.0011	---	---	---	---
Magnesium, total	7439-95-4	E420/WT	0.0050	mg/L	4.60	4.72	---	---	---	---
Manganese, total	7439-96-5	E420/WT	0.00010	mg/L	0.0179	0.00798	---	---	---	---
Molybdenum, total	7439-98-7	E420/WT	0.000050	mg/L	0.00159	0.00124	---	---	---	---
Nickel, total	7440-02-0	E420/WT	0.00050	mg/L	<0.00050	<0.00050	---	---	---	---



## Analytical Results

Sub-Matrix: Drinking Water

(Matrix: Water)

Analyte	CAS Number	Method/Lab	LOR	Unit	Client sample ID	Sample 1	Sample 2	---	---	---
					Client sampling date / time	18-Apr-2024 12:00	18-Apr-2024 13:15	---	---	---
					WT2409348-001	WT2409348-002	Result	Result	---	---
<b>Total Metals</b>										
Phosphorus, total	7723-14-0	E420/WT	0.050	mg/L	<0.050	<0.050	---	---	---	---
Potassium, total	7440-09-7	E420/WT	0.050	mg/L	3.70	3.41	---	---	---	---
Rubidium, total	7440-17-7	E420/WT	0.00020	mg/L	0.00154	0.00139	---	---	---	---
Selenium, total	7782-49-2	E420/WT	0.000050	mg/L	0.000232	0.000258	---	---	---	---
Silicon (as SiO <sub>2</sub> ), total	7631-86-9	EC420.SiO <sub>2</sub> /WT	0.25	mg/L	8.13	8.62	---	---	---	---
Silicon, total	7440-21-3	E420/WT	0.10	mg/L	3.80	4.03	---	---	---	---
Silver, total	7440-22-4	E420/WT	0.000010	mg/L	<0.000010	<0.000010	---	---	---	---
Sodium, total	7440-23-5	E420/WT	0.050	mg/L	2.87	2.91	---	---	---	---
Strontium, total	7440-24-6	E420/WT	0.00020	mg/L	0.655	0.654	---	---	---	---
Sulfur, total	7704-34-9	E420/WT	0.50	mg/L	3.27	3.23	---	---	---	---
Tellurium, total	13494-80-9	E420/WT	0.00020	mg/L	<0.00020	<0.00020	---	---	---	---
Thallium, total	7440-28-0	E420/WT	0.000010	mg/L	<0.000010	<0.000010	---	---	---	---
Thorium, total	7440-29-1	E420/WT	0.00010	mg/L	<0.00010	<0.00010	---	---	---	---
Tin, total	7440-31-5	E420/WT	0.00010	mg/L	<0.00010	<0.00010	---	---	---	---
Titanium, total	7440-32-6	E420/WT	0.00030	mg/L	0.00048	0.00037	---	---	---	---
Tungsten, total	7440-33-7	E420/WT	0.00010	mg/L	0.00016	0.00010	---	---	---	---
Uranium, total	7440-61-1	E420/WT	0.000010	mg/L	0.00239	0.00358	---	---	---	---
Vanadium, total	7440-62-2	E420/WT	0.00050	mg/L	0.00137	0.00287	---	---	---	---
Zinc, total	7440-66-6	E420/WT	0.0030	mg/L	<0.0030	<0.0030	---	---	---	---
Zirconium, total	7440-67-7	E420/WT	0.00020	mg/L	<0.00020	<0.00020	---	---	---	---

Please refer to the General Comments section for an explanation of any result qualifiers detected.

Please refer to the Accreditation section for an explanation of analyte accreditations.

## QUALITY CONTROL REPORT

Work Order	: <b>WT2409348</b>	Page	: 1 of 13
Client	: CF Crozier & Associates	Laboratory	: ALS Environmental - Waterloo
Contact	: Josie Gerrits	Account Manager	: Andrew Martin
Address	: 2800 High Point Drive Milton ON Canada L9T 6P4	Address	: 60 Northland Road, Unit 1 Waterloo, Ontario Canada N2V 2B8
Telephone	: ----	Telephone	: +1 519 886 6910
Project	: 2457-6768	Date Samples Received	: 19-Apr-2024 14:00
PO	: ----	Date Analysis Commenced	: 20-Apr-2024
C-O-C number	: ----	Issue Date	: 27-Apr-2024 16:12
Sampler	: ----		
Site	: ----		
Quote number	: 2024 SOA		
No. of samples received	: 2		
No. of samples analysed	: 2		

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percent Difference (RPD) and Data Quality Objectives
- Matrix Spike (MS) Report; Recovery and Data Quality Objectives
- Method Blank (MB) Report; Recovery and Data Quality Objectives
- Laboratory Control Sample (LCS) Report; Recovery and Data Quality Objectives

### Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is conducted in accordance with US FDA 21 CFR Part 11.

Signatories	Position	Laboratory Department
John Tang	Lab Analyst	Waterloo Inorganics, Waterloo, Ontario
Jon Fisher	Production Manager, Environmental	Waterloo Inorganics, Waterloo, Ontario
Kelly Fischer	Technical Specialist	Waterloo Inorganics, Waterloo, Ontario
Kelly Fischer	Technical Specialist	Waterloo Metals, Waterloo, Ontario
Nik Perkio	Inorganics Analyst	Waterloo Inorganics, Waterloo, Ontario
Nik Perkio	Inorganics Analyst	Waterloo Metals, Waterloo, Ontario
Zeba Patel	Analyst	Waterloo Microbiology, Waterloo, Ontario



## General Comments

The ALS Quality Control (QC) report is optionally provided to ALS clients upon request. ALS test methods include comprehensive QC checks with every analysis to ensure our high standards of quality are met. Each QC result has a known or expected target value, which is compared against predetermined Data Quality Objectives (DQOs) to provide confidence in the accuracy of associated test results. This report contains detailed results for all QC results applicable to this sample submission. Please refer to the ALS Quality Control Interpretation report (QCI) for applicable method references and methodology summaries.

### Key :

Anonymous = Refers to samples which are not part of this work order, but which formed part of the QC process lot.

CAS Number = Chemical Abstracts Service number is a unique identifier assigned to discrete substances.

DQO = Data Quality Objective.

LOR = Limit of Reporting (detection limit).

RPD = Relative Percent Difference

# = Indicates a QC result that did not meet the ALS DQO.

## Workorder Comments

---

Holding times are displayed as "—" if no guidance exists from CCME, Canadian provinces, or broadly recognized international references.

---

## Laboratory Duplicate (DUP) Report

A Laboratory Duplicate (DUP) is a randomly selected intralaboratory replicate sample. Laboratory Duplicates provide information regarding method precision and sample heterogeneity. ALS DQOs for Laboratory Duplicates are expressed as test-specific limits for Relative Percent Difference (RPD), or as an absolute difference limit of 2 times the LOR for low concentration duplicates within ~ 4-10 times the LOR (cut-off is test-specific).

Sub-Matrix: Water

Laboratory Duplicate (DUP) Report											
Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	LOR	Unit	Original Result	Duplicate Result	RPD(%) or Difference	Duplicate Limits	Qualifier
<b>Physical Tests (QC Lot: 1410394)</b>											
WT2409348-001	Anonymous	Turbidity	---	E121	0.10	NTU	23.6	23.8	0.842%	15%	---
<b>Physical Tests (QC Lot: 1411785)</b>											
WT2409348-001	Sample 1	Alkalinity, total (as CaCO <sub>3</sub> )	---	E290	1.0	mg/L	87.1	87.5	0.527%	20%	---
<b>Physical Tests (QC Lot: 1411786)</b>											
WT2409348-001	Sample 1	Conductivity	---	E100	1.0	µS/cm	185	183	1.08%	10%	---
<b>Physical Tests (QC Lot: 1411787)</b>											
WT2409348-001	Sample 1	pH	---	E108	0.10	pH units	8.16	8.22	0.733%	4%	---
<b>Physical Tests (QC Lot: 1413426)</b>											
WT2409348-001	Sample 1	Colour, apparent	---	E330	2.0	CU	49.0	53.4	8.46%	20%	---
<b>Physical Tests (QC Lot: 1416434)</b>											
WT2409348-001	Sample 1	Solids, total dissolved [TDS]	---	E162	13	mg/L	111	123	13	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411563)</b>											
HA2400775-001	Anonymous	Ammonia, total (as N)	7664-41-7	E298	0.500	mg/L	4.77	4.81	0.0472	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411779)</b>											
WT2409348-001	Sample 1	Bromide	24959-67-9	E235.Br	0.10	mg/L	<0.10	<0.10	0	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411780)</b>											
WT2409348-001	Sample 1	Fluoride	16984-48-8	E235.F	0.020	mg/L	0.118	0.120	0.002	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411781)</b>											
WT2409348-001	Sample 1	Nitrate (as N)	14797-55-8	E235.NO3	0.020	mg/L	0.024	0.025	0.002	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411782)</b>											
WT2409348-001	Sample 1	Nitrite (as N)	14797-65-0	E235.NO2	0.010	mg/L	<0.010	<0.010	0	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411783)</b>											
WT2409348-001	Sample 1	Chloride	16887-00-6	E235.Cl	0.50	mg/L	0.54	0.50	0.04	Diff <2x LOR	---
<b>Anions and Nutrients (QC Lot: 1411784)</b>											
WT2409348-001	Sample 1	Sulfate (as SO <sub>4</sub> )	14808-79-8	E235.SO4	0.30	mg/L	9.13	9.11	0.289%	20%	---
<b>Anions and Nutrients (QC Lot: 1411788)</b>											
HA2400788-001	Anonymous	Phosphate, ortho-, dissolved (as P)	14265-44-2	E378-U	0.0010	mg/L	<0.0010	<0.0010	0	Diff <2x LOR	---
<b>Microbiological Tests (QC Lot: 1410628)</b>											
WT2409348-001	Sample 1	Coliforms, total	---	E012.TC	1	CFU/100mL	1	<1	0	Diff <2x LOR	---
<b>Microbiological Tests (QC Lot: 1410629)</b>											



Sub-Matrix: Water					Laboratory Duplicate (DUP) Report						
Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	LOR	Unit	Original Result	Duplicate Result	RPD(%) or Difference	Duplicate Limits	Qualifier
<b>Microbiological Tests (QC Lot: 1410629) - continued</b>											
WT2409348-001	Sample 1	coliforms, total background	---	E012.BG.TC	1	CFU/100mL	4	# <1	3	Diff <2x LOR	---
<b>Microbiological Tests (QC Lot: 1410630)</b>											
WT2409341-001	Anonymous	Coliforms, Escherichia coli [E. coli]	---	E012A.EC	1	CFU/100mL	<1	<1	0	Diff <2x LOR	---
<b>Total Metals (QC Lot: 1411231)</b>											
WT2409348-001	Sample 1	Aluminum, total	7429-90-5	E420	0.0030	mg/L	0.0082	0.0075	0.0008	Diff <2x LOR	---
		Antimony, total	7440-36-0	E420	0.00010	mg/L	<0.00010	<0.00010	0	Diff <2x LOR	---
		Arsenic, total	7440-38-2	E420	0.00010	mg/L	<0.00010	<0.00010	0	Diff <2x LOR	---
		Barium, total	7440-39-3	E420	0.00010	mg/L	0.0391	0.0396	1.25%	20%	---
		Beryllium, total	7440-41-7	E420	0.000020	mg/L	<0.000020	<0.000020	0	Diff <2x LOR	---
		Bismuth, total	7440-69-9	E420	0.000050	mg/L	<0.000050	<0.000050	0	Diff <2x LOR	---
		Boron, total	7440-42-8	E420	0.010	mg/L	<0.010	<0.010	0	Diff <2x LOR	---
		Cadmium, total	7440-43-9	E420	0.0000050	mg/L	<0.0000050	<0.0000050	0	Diff <2x LOR	---
		Calcium, total	7440-70-2	E420	0.050	mg/L	25.3	25.3	0.0714%	20%	---
		Cesium, total	7440-46-2	E420	0.000010	mg/L	<0.000010	<0.000010	0	Diff <2x LOR	---
		Chromium, total	7440-47-3	E420	0.00050	mg/L	<0.00050	<0.00050	0	Diff <2x LOR	---
		Cobalt, total	7440-48-4	E420	0.00010	mg/L	<0.00010	<0.00010	0	Diff <2x LOR	---
		Copper, total	7440-50-8	E420	0.00050	mg/L	0.00104	0.00089	0.00015	Diff <2x LOR	---
		Iron, total	7439-89-6	E420	0.010	mg/L	0.787	0.783	0.419%	20%	---
		Lead, total	7439-92-1	E420	0.000050	mg/L	<0.000050	<0.000050	0	Diff <2x LOR	---
		Lithium, total	7439-93-2	E420	0.0010	mg/L	0.0014	0.0013	0.0001	Diff <2x LOR	---
		Magnesium, total	7439-95-4	E420	0.0050	mg/L	4.60	4.58	0.404%	20%	---
		Manganese, total	7439-96-5	E420	0.00010	mg/L	0.0179	0.0177	1.21%	20%	---
		Molybdenum, total	7439-98-7	E420	0.000050	mg/L	0.00159	0.00158	0.828%	20%	---
		Nickel, total	7440-02-0	E420	0.00050	mg/L	<0.00050	<0.00050	0	Diff <2x LOR	---
		Phosphorus, total	7723-14-0	E420	0.050	mg/L	<0.050	<0.050	0	Diff <2x LOR	---
		Potassium, total	7440-09-7	E420	0.050	mg/L	3.70	3.68	0.699%	20%	---
		Rubidium, total	7440-17-7	E420	0.00020	mg/L	0.00154	0.00156	0.00002	Diff <2x LOR	---
		Selenium, total	7782-49-2	E420	0.000050	mg/L	0.000232	0.000268	0.000036	Diff <2x LOR	---
		Silicon, total	7440-21-3	E420	0.10	mg/L	3.80	3.77	0.783%	20%	---
		Silver, total	7440-22-4	E420	0.000010	mg/L	<0.000010	<0.000010	0	Diff <2x LOR	---
		Sodium, total	7440-23-5	E420	0.050	mg/L	2.87	2.88	0.673%	20%	---
		Strontium, total	7440-24-6	E420	0.00020	mg/L	0.655	0.668	1.99%	20%	---
		Sulfur, total	7704-34-9	E420	0.50	mg/L	3.27	3.19	0.08	Diff <2x LOR	---
		Tellurium, total	13494-80-9	E420	0.00020	mg/L	<0.00020	<0.00020	0	Diff <2x LOR	---

Sub-Matrix: Water					Laboratory Duplicate (DUP) Report							
Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	LOR	Unit	Original Result	Duplicate Result	RPD(%) or Difference	Duplicate Limits	Qualifier	
<b>Total Metals (QC Lot: 1411231) - continued</b>												
WT2409348-001	Sample 1	Thallium, total	7440-28-0	E420	0.000010	mg/L	<0.000010	<0.000010	0	Diff <2x LOR	---	
		Thorium, total	7440-29-1	E420	0.00010	mg/L	<0.00010	<0.00010	0	Diff <2x LOR	---	
		Tin, total	7440-31-5	E420	0.00010	mg/L	<0.00010	<0.00010	0	Diff <2x LOR	---	
		Titanium, total	7440-32-6	E420	0.00030	mg/L	0.00048	0.00034	0.00014	Diff <2x LOR	---	
		Tungsten, total	7440-33-7	E420	0.00010	mg/L	0.00016	0.00016	0.000002	Diff <2x LOR	---	
		Uranium, total	7440-61-1	E420	0.000010	mg/L	0.00239	0.00244	1.89%	20%	---	
		Vanadium, total	7440-62-2	E420	0.00050	mg/L	0.00137	0.00139	0.00002	Diff <2x LOR	---	
		Zinc, total	7440-66-6	E420	0.0030	mg/L	<0.0030	<0.0030	0	Diff <2x LOR	---	
		Zirconium, total	7440-67-7	E420	0.00020	mg/L	<0.00020	<0.00020	0	Diff <2x LOR	---	

## Method Blank (MB) Report

A Method Blank is an analyte-free matrix that undergoes sample processing identical to that carried out for test samples. Method Blank results are used to monitor and control for potential contamination from the laboratory environment and reagents. For most tests, the DQO for Method Blanks is for the result to be < LOR.

Sub-Matrix: Water

Analyte	CAS Number	Method	LOR	Unit	Result	Qualifier
<b>Physical Tests (QCLot: 1410394)</b>						
Turbidity	---	E121	0.1	NTU	<0.10	---
<b>Physical Tests (QCLot: 1411785)</b>						
Alkalinity, total (as CaCO <sub>3</sub> )	---	E290	1	mg/L	<1.0	---
<b>Physical Tests (QCLot: 1411786)</b>						
Conductivity	---	E100	1	µS/cm	<1.0	---
<b>Physical Tests (QCLot: 1413426)</b>						
Colour, apparent	---	E330	2	CU	<2.0	---
<b>Physical Tests (QCLot: 1416434)</b>						
Solids, total dissolved [TDS]	---	E162	10	mg/L	<10	---
<b>Anions and Nutrients (QCLot: 1411563)</b>						
Ammonia, total (as N)	7664-41-7	E298	0.005	mg/L	<0.0050	---
<b>Anions and Nutrients (QCLot: 1411779)</b>						
Bromide	24959-67-9	E235.Br	0.1	mg/L	<0.10	---
<b>Anions and Nutrients (QCLot: 1411780)</b>						
Fluoride	16984-48-8	E235.F	0.02	mg/L	<0.020	---
<b>Anions and Nutrients (QCLot: 1411781)</b>						
Nitrate (as N)	14797-55-8	E235.NO3	0.02	mg/L	<0.020	---
<b>Anions and Nutrients (QCLot: 1411782)</b>						
Nitrite (as N)	14797-65-0	E235.NO2	0.01	mg/L	<0.010	---
<b>Anions and Nutrients (QCLot: 1411783)</b>						
Chloride	16887-00-6	E235.Cl	0.5	mg/L	<0.50	---
<b>Anions and Nutrients (QCLot: 1411784)</b>						
Sulfate (as SO <sub>4</sub> )	14808-79-8	E235.SO4	0.3	mg/L	<0.30	---
<b>Anions and Nutrients (QCLot: 1411788)</b>						
Phosphate, ortho-, dissolved (as P)	14265-44-2	E378-U	0.001	mg/L	<0.0010	---
<b>Microbiological Tests (QCLot: 1410628)</b>						
Coliforms, total	---	E012.TC	1	CFU/100mL	<1	---
<b>Microbiological Tests (QCLot: 1410629)</b>						
coliforms, total background	---	E012.BG.TC	1	CFU/100mL	<1	---
<b>Microbiological Tests (QCLot: 1410630)</b>						
Coliforms, Escherichia coli [E. coli]	---	E012A.EC	1	CFU/100mL	<1	---
<b>Total Metals (QCLot: 1411231)</b>						

Sub-Matrix: Water

Analyte	CAS Number	Method	LOR	Unit	Result	Qualifier
<b>Total Metals (QCLot: 1411231) - continued</b>						
Aluminum, total	7429-90-5	E420	0.003	mg/L	<0.0030	---
Antimony, total	7440-36-0	E420	0.0001	mg/L	<0.00010	---
Arsenic, total	7440-38-2	E420	0.0001	mg/L	<0.00010	---
Barium, total	7440-39-3	E420	0.0001	mg/L	<0.00010	---
Beryllium, total	7440-41-7	E420	0.00002	mg/L	<0.000020	---
Bismuth, total	7440-69-9	E420	0.00005	mg/L	<0.000050	---
Boron, total	7440-42-8	E420	0.01	mg/L	<0.010	---
Cadmium, total	7440-43-9	E420	0.000005	mg/L	<0.0000050	---
Calcium, total	7440-70-2	E420	0.05	mg/L	<0.050	---
Cesium, total	7440-46-2	E420	0.00001	mg/L	<0.000010	---
Chromium, total	7440-47-3	E420	0.0005	mg/L	<0.00050	---
Cobalt, total	7440-48-4	E420	0.0001	mg/L	<0.00010	---
Copper, total	7440-50-8	E420	0.0005	mg/L	<0.00050	---
Iron, total	7439-89-6	E420	0.01	mg/L	<0.010	---
Lead, total	7439-92-1	E420	0.00005	mg/L	<0.000050	---
Lithium, total	7439-93-2	E420	0.001	mg/L	<0.0010	---
Magnesium, total	7439-95-4	E420	0.005	mg/L	<0.0050	---
Manganese, total	7439-96-5	E420	0.0001	mg/L	<0.00010	---
Molybdenum, total	7439-98-7	E420	0.00005	mg/L	<0.000050	---
Nickel, total	7440-02-0	E420	0.0005	mg/L	<0.00050	---
Phosphorus, total	7723-14-0	E420	0.05	mg/L	<0.050	---
Potassium, total	7440-09-7	E420	0.05	mg/L	<0.050	---
Rubidium, total	7440-17-7	E420	0.0002	mg/L	<0.00020	---
Selenium, total	7782-49-2	E420	0.00005	mg/L	<0.000050	---
Silicon, total	7440-21-3	E420	0.1	mg/L	<0.10	---
Silver, total	7440-22-4	E420	0.00001	mg/L	<0.000010	---
Sodium, total	7440-23-5	E420	0.05	mg/L	<0.050	---
Strontium, total	7440-24-6	E420	0.0002	mg/L	<0.00020	---
Sulfur, total	7704-34-9	E420	0.5	mg/L	<0.50	---
Tellurium, total	13494-80-9	E420	0.0002	mg/L	<0.00020	---
Thallium, total	7440-28-0	E420	0.00001	mg/L	<0.000010	---
Thorium, total	7440-29-1	E420	0.0001	mg/L	<0.00010	---
Tin, total	7440-31-5	E420	0.0001	mg/L	<0.00010	---
Titanium, total	7440-32-6	E420	0.0003	mg/L	<0.00030	---
Tungsten, total	7440-33-7	E420	0.0001	mg/L	<0.00010	---

Sub-Matrix: Water

Analyte	CAS Number	Method	LOR	Unit	Result	Qualifier
<b>Total Metals (QCLot: 1411231) - continued</b>						
Uranium, total	7440-61-1	E420	0.00001	mg/L	<0.000010	---
Vanadium, total	7440-62-2	E420	0.0005	mg/L	<0.00050	---
Zinc, total	7440-66-6	E420	0.003	mg/L	<0.0030	---
Zirconium, total	7440-67-7	E420	0.0002	mg/L	<0.00020	---

## Laboratory Control Sample (LCS) Report

A Laboratory Control Sample (LCS) is an analyte-free matrix that has been fortified (spiked) with test analytes at known concentration and processed in an identical manner to test samples. LCS results are expressed as percent recovery, and are used to monitor and control test method accuracy and precision, independent of test sample matrix.

Sub-Matrix: Water

Analyte	CAS Number	Method	LOR	Unit	Laboratory Control Sample (LCS) Report				
					Spike	Recovery (%)	Recovery Limits (%)		Qualifier
<b>Physical Tests (QCLot: 1410394)</b>									
Turbidity	---	E121	0.1	NTU	200 NTU	103	85.0	115	---
<b>Physical Tests (QC Lot: 1411785)</b>									
Alkalinity, total (as CaCO <sub>3</sub> )	---	E290	1	mg/L	150 mg/L	102	85.0	115	---
<b>Physical Tests (QC Lot: 1411786)</b>									
Conductivity	---	E100	1	µS/cm	1410 µS/cm	105	90.0	110	---
<b>Physical Tests (QC Lot: 1411787)</b>									
pH	---	E108	---	pH units	7 pH units	100	98.0	102	---
<b>Physical Tests (QC Lot: 1413426)</b>									
Colour, apparent	---	E330	2	CU	25 CU	103	70.0	130	---
<b>Physical Tests (QC Lot: 1416434)</b>									
Solids, total dissolved [TDS]	---	E162	10	mg/L	1000 mg/L	90.7	85.0	115	---
<b>Anions and Nutrients (QC Lot: 1411563)</b>									
Ammonia, total (as N)	7664-41-7	E298	0.005	mg/L	0.2 mg/L	103	85.0	115	---
<b>Anions and Nutrients (QC Lot: 1411779)</b>									
Bromide	24959-67-9	E235.Br	0.1	mg/L	0.5 mg/L	95.4	85.0	115	---
<b>Anions and Nutrients (QC Lot: 1411780)</b>									
Fluoride	16984-48-8	E235.F	0.02	mg/L	1 mg/L	100	90.0	110	---
<b>Anions and Nutrients (QC Lot: 1411781)</b>									
Nitrate (as N)	14797-55-8	E235.NO3	0.02	mg/L	2.5 mg/L	98.9	90.0	110	---
<b>Anions and Nutrients (QC Lot: 1411782)</b>									
Nitrite (as N)	14797-65-0	E235.NO2	0.01	mg/L	0.5 mg/L	97.2	90.0	110	---
<b>Anions and Nutrients (QC Lot: 1411783)</b>									
Chloride	16887-00-6	E235.Cl	0.5	mg/L	100 mg/L	100.0	90.0	110	---
<b>Anions and Nutrients (QC Lot: 1411784)</b>									
Sulfate (as SO <sub>4</sub> )	14808-79-8	E235.SO4	0.3	mg/L	100 mg/L	101	90.0	110	---
<b>Anions and Nutrients (QC Lot: 1411788)</b>									
Phosphate, ortho-, dissolved (as P)	14265-44-2	E378-U	0.001	mg/L	0.031 mg/L	104	80.0	120	---
<b>Total Metals (QC Lot: 1411231)</b>									
Aluminum, total	7429-90-5	E420	0.003	mg/L	0.1 mg/L	99.5	80.0	120	---
Antimony, total	7440-36-0	E420	0.0001	mg/L	0.05 mg/L	102	80.0	120	---

Sub-Matrix: Water

Analyte	CAS Number	Method	LOR	Unit	Laboratory Control Sample (LCS) Report				
					Spike	Recovery (%)	Recovery Limits (%)		Qualifier
<b>Total Metals (QCLot: 1411231) - continued</b>									
Arsenic, total	7440-38-2	E420	0.0001	mg/L	0.05 mg/L	106	80.0	120	---
Barium, total	7440-39-3	E420	0.0001	mg/L	0.012 mg/L	102	80.0	120	---
Beryllium, total	7440-41-7	E420	0.00002	mg/L	0.005 mg/L	92.6	80.0	120	---
Bismuth, total	7440-69-9	E420	0.00005	mg/L	0.05 mg/L	96.9	80.0	120	---
Boron, total	7440-42-8	E420	0.01	mg/L	0.05 mg/L	93.9	80.0	120	---
Cadmium, total	7440-43-9	E420	0.000005	mg/L	0.005 mg/L	97.8	80.0	120	---
Calcium, total	7440-70-2	E420	0.05	mg/L	2.5 mg/L	96.1	80.0	120	---
Cesium, total	7440-46-2	E420	0.00001	mg/L	0.002 mg/L	101	80.0	120	---
Chromium, total	7440-47-3	E420	0.0005	mg/L	0.012 mg/L	103	80.0	120	---
Cobalt, total	7440-48-4	E420	0.0001	mg/L	0.012 mg/L	103	80.0	120	---
Copper, total	7440-50-8	E420	0.0005	mg/L	0.012 mg/L	103	80.0	120	---
Iron, total	7439-89-6	E420	0.01	mg/L	0.05 mg/L	99.3	80.0	120	---
Lead, total	7439-92-1	E420	0.00005	mg/L	0.025 mg/L	96.5	80.0	120	---
Lithium, total	7439-93-2	E420	0.001	mg/L	0.012 mg/L	87.0	80.0	120	---
Magnesium, total	7439-95-4	E420	0.005	mg/L	2.5 mg/L	109	80.0	120	---
Manganese, total	7439-96-5	E420	0.0001	mg/L	0.012 mg/L	103	80.0	120	---
Molybdenum, total	7439-98-7	E420	0.00005	mg/L	0.012 mg/L	102	80.0	120	---
Nickel, total	7440-02-0	E420	0.0005	mg/L	0.025 mg/L	103	80.0	120	---
Phosphorus, total	7723-14-0	E420	0.05	mg/L	0.5 mg/L	108	80.0	120	---
Potassium, total	7440-09-7	E420	0.05	mg/L	2.5 mg/L	101	80.0	120	---
Rubidium, total	7440-17-7	E420	0.0002	mg/L	0.005 mg/L	102	80.0	120	---
Selenium, total	7782-49-2	E420	0.00005	mg/L	0.05 mg/L	102	80.0	120	---
Silicon, total	7440-21-3	E420	0.1	mg/L	0.5 mg/L	102	80.0	120	---
Silver, total	7440-22-4	E420	0.00001	mg/L	0.005 mg/L	91.7	80.0	120	---
Sodium, total	7440-23-5	E420	0.05	mg/L	2.5 mg/L	107	80.0	120	---
Strontium, total	7440-24-6	E420	0.0002	mg/L	0.012 mg/L	99.7	80.0	120	---
Sulfur, total	7704-34-9	E420	0.5	mg/L	2.5 mg/L	104	80.0	120	---
Tellurium, total	13494-80-9	E420	0.0002	mg/L	0.005 mg/L	100	80.0	120	---
Thallium, total	7440-28-0	E420	0.00001	mg/L	0.05 mg/L	99.5	80.0	120	---
Thorium, total	7440-29-1	E420	0.0001	mg/L	0.005 mg/L	94.3	80.0	120	---
Tin, total	7440-31-5	E420	0.0001	mg/L	0.025 mg/L	97.8	80.0	120	---
Titanium, total	7440-32-6	E420	0.0003	mg/L	0.012 mg/L	96.0	80.0	120	---
Tungsten, total	7440-33-7	E420	0.0001	mg/L	0.005 mg/L	97.2	80.0	120	---
Uranium, total	7440-61-1	E420	0.00001	mg/L	0 mg/L	95.4	80.0	120	---
Vanadium, total	7440-62-2	E420	0.0005	mg/L	0.025 mg/L	105	80.0	120	---
Zinc, total	7440-66-6	E420	0.003	mg/L	0.025 mg/L	101	80.0	120	---



Sub-Matrix: Water						Laboratory Control Sample (LCS) Report				
						Spike	Recovery (%)	Recovery Limits (%)		
Analyte	CAS Number	Method	LOR	Unit	Target Concentration	LCS	Low	High	Qualifier	
<b>Total Metals (QCLot: 1411231) - continued</b>										
Zirconium, total	7440-67-7	E420	0.0002	mg/L	0.005 mg/L	95.6	80.0	120	----	



## Matrix Spike (MS) Report

A Matrix Spike (MS) is a randomly selected intra-laboratory replicate sample that has been fortified (spiked) with test analytes at known concentration, and processed in an identical manner to test samples. Matrix Spikes provide information regarding analyte recovery and potential matrix effects. MS DQO exceedances due to sample matrix may sometimes be unavoidable; in such cases, test results for the associated sample (or similar samples) may be subject to bias. ND – Recovery not determined, background level >= 1x spike level.

Sub-Matrix: Water

Matrix Spike (MS) Report										
Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	Spike		Recovery (%)	Recovery Limits (%)		Qualifier
					Concentration	Target	MS	Low	High	
<b>Anions and Nutrients (QCLot: 1411563)</b>										
HA2400775-001	Anonymous	Ammonia, total (as N)	7664-41-7	E298	ND mg/L	---	ND	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411779)</b>										
WT2409348-001	Sample 1	Bromide	24959-67-9	E235.Br	0.47 mg/L	0.5 mg/L	93.2	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411780)</b>										
WT2409348-001	Sample 1	Fluoride	16984-48-8	E235.F	1.10 mg/L	1 mg/L	110	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411781)</b>										
WT2409348-001	Sample 1	Nitrate (as N)	14797-55-8	E235.NO3	2.44 mg/L	2.5 mg/L	97.7	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411782)</b>										
WT2409348-001	Sample 1	Nitrite (as N)	14797-65-0	E235.NO2	0.479 mg/L	0.5 mg/L	95.8	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411783)</b>										
WT2409348-001	Sample 1	Chloride	16887-00-6	E235.Cl	99.3 mg/L	100 mg/L	99.3	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411784)</b>										
WT2409348-001	Sample 1	Sulfate (as SO4)	14808-79-8	E235.SO4	98.7 mg/L	100 mg/L	98.7	75.0	125	---
<b>Anions and Nutrients (QCLot: 1411788)</b>										
HA2400788-001	Anonymous	Phosphate, ortho-, dissolved (as P)	14265-44-2	E378-U	0.0190 mg/L	0.02 mg/L	96.8	70.0	130	---
<b>Total Metals (QCLot: 1411231)</b>										
WT2409348-002	Sample 2	Aluminum, total	7429-90-5	E420	0.0949 mg/L	0.1 mg/L	94.9	70.0	130	---
		Antimony, total	7440-36-0	E420	0.0537 mg/L	0.05 mg/L	107	70.0	130	---
		Arsenic, total	7440-38-2	E420	0.0533 mg/L	0.05 mg/L	106	70.0	130	---
		Barium, total	7440-39-3	E420	ND mg/L	---	ND	70.0	130	---
		Beryllium, total	7440-41-7	E420	0.00456 mg/L	0.005 mg/L	91.2	70.0	130	---
		Bismuth, total	7440-69-9	E420	0.0496 mg/L	0.05 mg/L	99.2	70.0	130	---
		Boron, total	7440-42-8	E420	0.047 mg/L	0.05 mg/L	93.3	70.0	130	---
		Cadmium, total	7440-43-9	E420	0.00511 mg/L	0.005 mg/L	102	70.0	130	---
		Calcium, total	7440-70-2	E420	ND mg/L	---	ND	70.0	130	---
		Cesium, total	7440-46-2	E420	0.00255 mg/L	0.002 mg/L	102	70.0	130	---
		Chromium, total	7440-47-3	E420	0.0138 mg/L	0.012 mg/L	110	70.0	130	---
		Cobalt, total	7440-48-4	E420	0.0128 mg/L	0.012 mg/L	103	70.0	130	---
		Copper, total	7440-50-8	E420	0.0127 mg/L	0.012 mg/L	102	70.0	130	---
		Iron, total	7439-89-6	E420	ND mg/L	---	ND	70.0	130	---
		Lead, total	7439-92-1	E420	0.0250 mg/L	0.025 mg/L	100	70.0	130	---
		Lithium, total	7439-93-2	E420	0.0108 mg/L	0.012 mg/L	86.7	70.0	130	---
		Magnesium, total	7439-95-4	E420	ND mg/L	---	ND	70.0	130	---
		Manganese, total	7439-96-5	E420	0.0121 mg/L	0.012 mg/L	97.0	70.0	130	---
		Molybdenum, total	7439-98-7	E420	0.0129 mg/L	0.012 mg/L	103	70.0	130	---

Sub-Matrix: Water

					Matrix Spike (MS) Report						
Laboratory sample ID	Client sample ID	Analyte	CAS Number	Method	Spike		Recovery (%)	Recovery Limits (%)		Qualifier	
					Concentration	Target		MS	Low	High	
<b>Total Metals (QC Lot: 1411231) - continued</b>											
WT2409348-002	Sample 2	Nickel, total	7440-02-0	E420	0.0254 mg/L	0.025 mg/L	102	70.0	130	---	---
		Phosphorus, total	7723-14-0	E420	0.531 mg/L	0.5 mg/L	106	70.0	130	---	---
		Potassium, total	7440-09-7	E420	ND mg/L	---	ND	70.0	130	---	---
		Rubidium, total	7440-17-7	E420	0.00506 mg/L	0.005 mg/L	101	70.0	130	---	---
		Selenium, total	7782-49-2	E420	0.0523 mg/L	0.05 mg/L	105	70.0	130	---	---
		Silicon, total	7440-21-3	E420	ND mg/L	---	ND	70.0	130	---	---
		Silver, total	7440-22-4	E420	0.00454 mg/L	0.005 mg/L	90.8	70.0	130	---	---
		Sodium, total	7440-23-5	E420	ND mg/L	---	ND	70.0	130	---	---
		Strontium, total	7440-24-6	E420	ND mg/L	---	ND	70.0	130	---	---
		Sulfur, total	7704-34-9	E420	ND mg/L	---	ND	70.0	130	---	---
		Tellurium, total	13494-80-9	E420	0.00482 mg/L	0.005 mg/L	96.4	70.0	130	---	---
		Thallium, total	7440-28-0	E420	0.0498 mg/L	0.05 mg/L	99.5	70.0	130	---	---
		Thorium, total	7440-29-1	E420	0.00494 mg/L	0.005 mg/L	98.9	70.0	130	---	---
		Tin, total	7440-31-5	E420	0.0252 mg/L	0.025 mg/L	101	70.0	130	---	---
		Titanium, total	7440-32-6	E420	0.0124 mg/L	0.012 mg/L	99.2	70.0	130	---	---
		Tungsten, total	7440-33-7	E420	0.00501 mg/L	0.005 mg/L	100	70.0	130	---	---
		Uranium, total	7440-61-1	E420	ND mg/L	---	ND	70.0	130	---	---
		Vanadium, total	7440-62-2	E420	0.0261 mg/L	0.025 mg/L	104	70.0	130	---	---
		Zinc, total	7440-66-6	E420	0.0249 mg/L	0.025 mg/L	99.7	70.0	130	---	---
		Zirconium, total	7440-67-7	E420	0.00487 mg/L	0.005 mg/L	97.5	70.0	130	---	---

## QUALITY CONTROL INTERPRETIVE REPORT

Work Order	: WT2409348	Page	: 1 of 13
Client	: CF Crozier & Associates	Laboratory	: ALS Environmental - Waterloo
Contact	: Josie Gerrits	Account Manager	: Andrew Martin
Address	: 2800 High Point Drive Milton ON Canada L9T 6P4	Address	: 60 Northland Road, Unit 1 Waterloo, Ontario Canada N2V 2B8
Telephone	: ----	Telephone	: +1 519 886 6910
Project	: 2457-6768	Date Samples Received	: 19-Apr-2024 14:00
PO	: ----	Issue Date	: 27-Apr-2024 16:12
C-O-C number	: ----		
Sampler	: ----		
Site	: ----		
Quote number	: 2024 SOA		
No. of samples received	: 2		
No. of samples analysed	: 2		

This report is automatically generated by the ALS LIMS (Laboratory Information Management System) through evaluation of Quality Control (QC) results and other QA parameters associated with this submission, and is intended to facilitate rapid data validation by auditors or reviewers. The report highlights any exceptions and outliers to ALS Data Quality Objectives, provides holding time details and exceptions, summarizes QC sample frequencies, and lists applicable methodology references and summaries.

**Key**

Anonymous: Refers to samples which are not part of this work order, but which formed part of the QC process lot.

CAS Number: Chemical Abstracts Service number is a unique identifier assigned to discrete substances.

DQO: Data Quality Objective.

LOR: Limit of Reporting (detection limit).

RPD: Relative Percent Difference.

### Workorder Comments

Holding times are displayed as "----" if no guidance exists from CCME, Canadian provinces, or broadly recognized international references.

### Summary of Outliers

#### Outliers : Quality Control Samples

- No Method Blank value outliers occur.
- No Laboratory Control Sample (LCS) outliers occur
- No Matrix Spike outliers occur.
- Duplicate outliers occur - please see following pages for full details.
- No Test sample Surrogate recovery outliers exist.

#### Outliers: Reference Material (RM) Samples

- No Reference Material (RM) Sample outliers occur.

### ***Outliers : Analysis Holding Time Compliance (Breaches)***

- Analysis Holding Time Outliers exist - please see following pages for full details.

### ***Outliers : Frequency of Quality Control Samples***

- No Quality Control Sample Frequency Outliers occur.

### Outliers : Quality Control Samples

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

#### Matrix: Water

Analyte Group	Laboratory sample ID	Client/Ref Sample ID	Analyte	CAS Number	Method	Result	Limits	Comment
<b>Duplicate (DUP) RPDs</b>								
Microbiological Tests	WT2409348-001	Sample 1	coliforms, total background	----	E012.BG.TC	3 %	Diff <2x LOR	Low Level DUP DQO exceeded (difference > 2 LOR).

## Analysis Holding Time Compliance

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times, which are selected to meet known provincial and/or federal requirements. In the absence of regulatory hold times, ALS establishes recommendations based on guidelines published by organizations such as CCME, US EPA, APHA Standard Methods, ASTM, or Environment Canada (where available). Dates and holding times reported below represent the first dates of extraction or analysis. If subsequent tests or dilutions exceeded holding times, qualifiers are added (refer to COA).

If samples are identified below as having been analyzed or extracted outside of recommended holding times, measurement uncertainties may be increased, and this should be taken into consideration when interpreting results.

Where actual sampling date is not provided on the chain of custody, the date of receipt with time at 00:00 is used for calculation purposes.

Where only the sample date without time is provided on the chain of custody, the sampling date at 00:00 is used for calculation purposes.

Matrix: Water										Evaluation: ✖ = Holding time exceedance ; ✓ = Within Holding Time																
Analyte Group : Analytical Method	Container / Client Sample ID(s)	Method	Sampling Date	Extraction / Preparation				Analysis																		
				Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval	Rec	Actual													
Anions and Nutrients : Ammonia by Fluorescence																										
Amber glass total (sulfuric acid) [ON MECP]		E298	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 1																										
Anions and Nutrients : Ammonia by Fluorescence																										
Amber glass total (sulfuric acid) [ON MECP]		E298	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 2																										
Anions and Nutrients : Bromide in Water by IC																										
HDPE [ON MECP]		E235.Br	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 1																										
Anions and Nutrients : Bromide in Water by IC																										
HDPE [ON MECP]		E235.Br	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 2																										
Anions and Nutrients : Chloride in Water by IC																										
HDPE [ON MECP]		E235.Cl	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 1																										
Anions and Nutrients : Chloride in Water by IC																										
HDPE [ON MECP]		E235.Cl	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓	Rec	Actual													
Sample 2																										
Anions and Nutrients : Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)																										
HDPE [ON MECP]		E378-U	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓	Rec	Actual													
Sample 1																										

Matrix: Water Evaluation: ✘ = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method	Method	Sampling Date	Extraction / Preparation				Analysis			
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval
				Rec	Actual			Rec	Actual	
<b>Anions and Nutrients : Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)</b>										
HDPE [ON MECP] Sample 2	E378-U	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓
<b>Anions and Nutrients : Fluoride in Water by IC</b>										
HDPE [ON MECP] Sample 1	E235.F	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓
<b>Anions and Nutrients : Fluoride in Water by IC</b>										
HDPE [ON MECP] Sample 2	E235.F	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓
<b>Anions and Nutrients : Nitrate in Water by IC</b>										
HDPE [ON MECP] Sample 1	E235.NO3	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓
<b>Anions and Nutrients : Nitrate in Water by IC</b>										
HDPE [ON MECP] Sample 2	E235.NO3	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓
<b>Anions and Nutrients : Nitrite in Water by IC</b>										
HDPE [ON MECP] Sample 1	E235.NO2	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓
<b>Anions and Nutrients : Nitrite in Water by IC</b>										
HDPE [ON MECP] Sample 2	E235.NO2	18-Apr-2024	22-Apr-2024	7 days	4 days	✓	23-Apr-2024	7 days	5 days	✓
<b>Anions and Nutrients : Sulfate in Water by IC</b>										
HDPE [ON MECP] Sample 1	E235.SO4	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓
<b>Anions and Nutrients : Sulfate in Water by IC</b>										
HDPE [ON MECP] Sample 2	E235.SO4	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓

Matrix: Water Evaluation: ✗ = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method	Method	Sampling Date	Extraction / Preparation				Analysis			
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval
				Rec	Actual			Rec	Actual	
<b>Microbiological Tests : E. coli (MF-mFC-BCIG)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 2	E012A.EC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	46 hrs	✓
<b>Microbiological Tests : E. coli (MF-mFC-BCIG)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 1	E012A.EC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	48 hrs	✓
<b>Microbiological Tests : Total Coliforms (MF-mEndo)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 2	E012.TC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	46 hrs	✓
<b>Microbiological Tests : Total Coliforms (MF-mEndo)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 1	E012.TC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	48 hrs	✓
<b>Microbiological Tests : Total Coliforms Background (MF-mEndo)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 2	E012.BG.TC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	46 hrs	✓
<b>Microbiological Tests : Total Coliforms Background (MF-mEndo)</b>										
Sterile HDPE (Sodium thiosulphate) [ON MECP] Sample 1	E012.BG.TC	18-Apr-2024	---	---	---		20-Apr-2024	48 hrs	48 hrs	✓
<b>Physical Tests : Alkalinity Species by Titration</b>										
HDPE [ON MECP] Sample 1	E290	18-Apr-2024	22-Apr-2024	14 days	4 days	✓	23-Apr-2024	14 days	5 days	✓
<b>Physical Tests : Alkalinity Species by Titration</b>										
HDPE [ON MECP] Sample 2	E290	18-Apr-2024	22-Apr-2024	14 days	4 days	✓	23-Apr-2024	14 days	5 days	✓
<b>Physical Tests : Colour (Apparent) by Spectrometer</b>										
HDPE [ON MECP] Sample 2	E330	18-Apr-2024	---	---	---		23-Apr-2024	48 hrs	123 hrs	✗ EHTL



Matrix: Water Evaluation: ✗ = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method	Method	Sampling Date	Extraction / Preparation				Analysis			
			Preparation Date	Holding Times	Eval	Analysis Date	Holding Times	Eval		
Container / Client Sample ID(s)	Rec	Actual	Rec	Actual		Rec	Actual	Eval		
<b>Physical Tests : Colour (Apparent) by Spectrometer</b>										
HDPE [ON MECP] Sample 1	E330	18-Apr-2024	----	----	----		23-Apr-2024	48 hrs	124 hrs	✗ EHTL
<b>Physical Tests : Conductivity in Water</b>										
HDPE [ON MECP] Sample 1	E100	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓
<b>Physical Tests : Conductivity in Water</b>										
HDPE [ON MECP] Sample 2	E100	18-Apr-2024	22-Apr-2024	28 days	4 days	✓	23-Apr-2024	28 days	5 days	✓
<b>Physical Tests : pH by Meter</b>										
HDPE [ON MECP] Sample 1	E108	18-Apr-2024	22-Apr-2024	14 days	4 days	✓	23-Apr-2024	14 days	5 days	✓
<b>Physical Tests : pH by Meter</b>										
HDPE [ON MECP] Sample 2	E108	18-Apr-2024	22-Apr-2024	14 days	4 days	✓	23-Apr-2024	14 days	5 days	✓
<b>Physical Tests : TDS by Gravimetry</b>										
HDPE [ON MECP] Sample 1	E162	18-Apr-2024	----	----	----		25-Apr-2024	7 days	7 days	✓
<b>Physical Tests : TDS by Gravimetry</b>										
HDPE [ON MECP] Sample 2	E162	18-Apr-2024	----	----	----		25-Apr-2024	7 days	7 days	✓
<b>Physical Tests : Turbidity by Nephelometry</b>										
HDPE [ON MECP] Sample 2	E121	18-Apr-2024	----	----	----		20-Apr-2024	48 hrs	43 hrs	✓
<b>Physical Tests : Turbidity by Nephelometry</b>										
HDPE [ON MECP] Sample 1	E121	18-Apr-2024	----	----	----		20-Apr-2024	48 hrs	44 hrs	✓

Matrix: Water Evaluation: ✗ = Holding time exceedance ; ✓ = Within Holding Time

Analyte Group : Analytical Method	Method	Sampling Date	Extraction / Preparation			Analysis				
			Preparation Date	Holding Times		Eval	Analysis Date	Holding Times		Eval
				Rec	Actual			Rec	Actual	
<b>Total Metals : Total Metals in Water by CRC ICPMS</b>										
HDPE total (nitric acid) Sample 1	E420	18-Apr-2024	22-Apr-2024	180 days	4 days	✓	22-Apr-2024	180 days	4 days	✓
<b>Total Metals : Total Metals in Water by CRC ICPMS</b>										
HDPE total (nitric acid) Sample 2	E420	18-Apr-2024	22-Apr-2024	180 days	4 days	✓	22-Apr-2024	180 days	4 days	✓

Legend & Qualifier Definitions

EHTL: Exceeded ALS recommended hold time prior to analysis. Sample was received less than 24 hours prior to expiry.

Rec. HT: ALS recommended hold time (see units).

## Quality Control Parameter Frequency Compliance

The following report summarizes the frequency of laboratory QC samples analyzed within the analytical batches (QC lots) in which the submitted samples were processed. The actual frequency should be greater than or equal to the expected frequency.

Matrix: Water

Evaluation: ✗ = QC frequency outside specification; ✓ = QC frequency within specification.

Quality Control Sample Type	Analytical Methods	Method	QC Lot #	Count		Frequency (%)		Evaluation
				QC	Regular	Actual	Expected	
<b>Laboratory Duplicates (DUP)</b>								
Alkalinity Species by Titration		E290	1411785	1	20	5.0	5.0	✓
Ammonia by Fluorescence		E298	1411563	1	20	5.0	5.0	✓
Bromide in Water by IC		E235.Br	1411779	1	2	50.0	5.0	✓
Chloride in Water by IC		E235.Cl	1411783	1	20	5.0	5.0	✓
Colour (Apparent) by Spectrometer		E330	1413426	1	14	7.1	5.0	✓
Conductivity in Water		E100	1411786	1	20	5.0	5.0	✓
Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)		E378-U	1411788	1	13	7.6	5.0	✓
E. coli (MF-mFC-BCIG)		E012A.EC	1410630	1	11	9.0	5.0	✓
Fluoride in Water by IC		E235.F	1411780	1	10	10.0	5.0	✓
Nitrate in Water by IC		E235.NO3	1411781	1	20	5.0	5.0	✓
Nitrite in Water by IC		E235.NO2	1411782	1	20	5.0	5.0	✓
pH by Meter		E108	1411787	1	20	5.0	5.0	✓
Sulfate in Water by IC		E235.SO4	1411784	1	20	5.0	5.0	✓
TDS by Gravimetry		E162	1416434	1	20	5.0	5.0	✓
Total Coliforms (MF-mEndo)		E012.TC	1410628	1	6	16.6	5.0	✓
Total Coliforms Background (MF-mEndo)		E012.BG.TC	1410629	1	5	20.0	5.0	✓
Total Metals in Water by CRC ICPMS		E420	1411231	1	20	5.0	5.0	✓
Turbidity by Nephelometry		E121	1410394	1	13	7.6	5.0	✓
<b>Laboratory Control Samples (LCS)</b>								
Alkalinity Species by Titration		E290	1411785	1	20	5.0	5.0	✓
Ammonia by Fluorescence		E298	1411563	1	20	5.0	5.0	✓
Bromide in Water by IC		E235.Br	1411779	1	2	50.0	5.0	✓
Chloride in Water by IC		E235.Cl	1411783	1	20	5.0	5.0	✓
Colour (Apparent) by Spectrometer		E330	1413426	1	14	7.1	5.0	✓
Conductivity in Water		E100	1411786	1	20	5.0	5.0	✓
Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)		E378-U	1411788	1	13	7.6	5.0	✓
Fluoride in Water by IC		E235.F	1411780	1	10	10.0	5.0	✓
Nitrate in Water by IC		E235.NO3	1411781	1	20	5.0	5.0	✓
Nitrite in Water by IC		E235.NO2	1411782	1	20	5.0	5.0	✓
pH by Meter		E108	1411787	1	20	5.0	5.0	✓
Sulfate in Water by IC		E235.SO4	1411784	1	20	5.0	5.0	✓
TDS by Gravimetry		E162	1416434	1	20	5.0	5.0	✓
Total Metals in Water by CRC ICPMS		E420	1411231	1	20	5.0	5.0	✓
Turbidity by Nephelometry		E121	1410394	1	13	7.6	5.0	✓
<b>Method Blanks (MB)</b>								

## Matrix: Water

Evaluation: **x** = QC frequency outside specification; **✓** = QC frequency within specification.

Quality Control Sample Type	Method	QC Lot #	Count		Frequency (%)		
Analytical Methods	Method	QC Lot #	QC	Regular	Actual	Expected	Evaluation
<b>Method Blanks (MB) - Continued</b>							
Alkalinity Species by Titration	E290	1411785	1	20	5.0	5.0	✓
Ammonia by Fluorescence	E298	1411563	1	20	5.0	5.0	✓
Bromide in Water by IC	E235.Br	1411779	1	2	50.0	5.0	✓
Chloride in Water by IC	E235.Cl	1411783	1	20	5.0	5.0	✓
Colour (Apparent) by Spectrometer	E330	1413426	1	14	7.1	5.0	✓
Conductivity in Water	E100	1411786	1	20	5.0	5.0	✓
Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)	E378-U	1411788	1	13	7.6	5.0	✓
E. coli (MF-mFC-BCIG)	E012A.EC	1410630	1	11	9.0	5.0	✓
Fluoride in Water by IC	E235.F	1411780	1	10	10.0	5.0	✓
Nitrate in Water by IC	E235.NO3	1411781	1	20	5.0	5.0	✓
Nitrite in Water by IC	E235.NO2	1411782	1	20	5.0	5.0	✓
Sulfate in Water by IC	E235.SO4	1411784	1	20	5.0	5.0	✓
TDS by Gravimetry	E162	1416434	1	20	5.0	5.0	✓
Total Coliforms (MF-mEndo)	E012.TC	1410628	1	6	16.6	5.0	✓
Total Coliforms Background (MF-mEndo)	E012.BG.TC	1410629	1	5	20.0	5.0	✓
Total Metals in Water by CRC ICPMS	E420	1411231	1	20	5.0	5.0	✓
Turbidity by Nephelometry	E121	1410394	1	13	7.6	5.0	✓
<b>Matrix Spikes (MS)</b>							
Ammonia by Fluorescence	E298	1411563	1	20	5.0	5.0	✓
Bromide in Water by IC	E235.Br	1411779	1	2	50.0	5.0	✓
Chloride in Water by IC	E235.Cl	1411783	1	20	5.0	5.0	✓
Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)	E378-U	1411788	1	13	7.6	5.0	✓
Fluoride in Water by IC	E235.F	1411780	1	10	10.0	5.0	✓
Nitrate in Water by IC	E235.NO3	1411781	1	20	5.0	5.0	✓
Nitrite in Water by IC	E235.NO2	1411782	1	20	5.0	5.0	✓
Sulfate in Water by IC	E235.SO4	1411784	1	20	5.0	5.0	✓
Total Metals in Water by CRC ICPMS	E420	1411231	1	20	5.0	5.0	✓

## Methodology References and Summaries

The analytical methods used by ALS are developed using internationally recognized reference methods (where available), such as those published by US EPA, APHA Standard Methods, ASTM, ISO, Environment Canada, BC MOE, and Ontario MOE. Reference methods may incorporate modifications to improve performance (indicated by "mod").

Analytical Methods				
	Method / Lab	Matrix	Method Reference	Method Descriptions
Total Coliforms Background (MF-mEndo)	E012.BG.TC  ALS Environmental - Waterloo	Water	APHA 9222B (mod)	Noncoliform bacteria observed on Total Coliform plates are enumerated.
Total Coliforms (MF-mEndo)	E012.TC  ALS Environmental - Waterloo	Water	APHA 9222B (mod)	Following filtration (0.45 µm), and incubation at 35.0 ± 0.5°C for 24 hours, colonies exhibiting characteristic morphology of the target organism are enumerated and confirmed.
E. coli (MF-mFC-BCIG)	E012A.EC  ALS Environmental - Waterloo	Water	ON E3433 (mod)	Following filtration (0.45 µm), and incubation at 44.5 ± 0.2°C for 24 hours, colonies exhibiting characteristic morphology of the target organism are enumerated.
Conductivity in Water	E100  ALS Environmental - Waterloo	Water	APHA 2510 (mod)	Conductivity, also known as Electrical Conductivity (EC) or Specific Conductance, is measured by immersion of a conductivity cell with platinum electrodes into a water sample. Conductivity measurements are temperature-compensated to 25°C.
pH by Meter	E108  ALS Environmental - Waterloo	Water	APHA 4500-H (mod)	pH is determined by potentiometric measurement with a pH electrode, and is conducted at ambient laboratory temperature (normally 20 ± 5°C). For high accuracy test results, pH should be measured in the field within the recommended 15 minute hold time.
Turbidity by Nephelometry	E121  ALS Environmental - Waterloo	Water	APHA 2130 B (mod)	Turbidity is measured by the nephelometric method, by measuring the intensity of light scatter under defined conditions.
TDS by Gravimetry	E162  ALS Environmental - Waterloo	Water	APHA 2540 C (mod)	Total Dissolved Solids (TDS) are determined by filtering a sample through a glass fibre filter, with evaporation of the filtrate at 180 ± 2°C for 16 hours or to constant weight, with gravimetric measurement of the residue.
Bromide in Water by IC	E235.Br  ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.
Chloride in Water by IC	E235.Cl  ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.
Fluoride in Water by IC	E235.F  ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.

Analytical Methods				
	Method / Lab	Matrix	Method Reference	Method Descriptions
Nitrite in Water by IC	E235.NO2 ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.
Nitrate in Water by IC	E235.NO3 ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.
Sulfate in Water by IC	E235.SO4 ALS Environmental - Waterloo	Water	EPA 300.1 (mod)	Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.
Alkalinity Species by Titration	E290 ALS Environmental - Waterloo	Water	APHA 2320 B (mod)	Total alkalinity is determined by potentiometric titration to a pH 4.5 endpoint. Bicarbonate, carbonate and hydroxide alkalinity are calculated from phenolphthalein alkalinity and total alkalinity values.
Ammonia by Fluorescence	E298 ALS Environmental - Waterloo	Water	Method Fialab 100, 2018	Ammonia in water is determined by automated continuous flow analysis with membrane diffusion and fluorescence detection, after reaction with OPA (ortho-phthalaldehyde). This method is approved under US EPA 40 CFR Part 136 (May 2021)
Colour (Apparent) by Spectrometer	E330 ALS Environmental - Waterloo	Water	APHA 2120 C (mod)	Colour (Apparent) is measured in an unfiltered sample spectrophotometrically using the single wavelength method. The colour contribution of settleable solids are not included in the result. This method is intended for potable waters.  Colour measurements can be highly pH dependent, and apply to the pH of the sample as received (at time of testing), without pH adjustment.
Dissolved Orthophosphate by Colourimetry (Ultra Trace Level 0.001 mg/L)	E378-U ALS Environmental - Waterloo	Water	APHA 4500-P F (mod)	Dissolved Orthophosphate is determined colourimetrically on a sample that has been lab or field filtered through a 0.45 micron membrane filter.  Field filtration is recommended to ensure test results represent conditions at time of sampling.
Total Metals in Water by CRC ICPMS	E420 ALS Environmental - Waterloo	Water	EPA 200.2/6020B (mod)	Water samples are digested with nitric and hydrochloric acids, and analyzed by Collision/Reaction Cell ICPMS.  Method Limitation (re: Sulfur): Sulfide and volatile sulfur species may not be recovered by this method.
Hardness (Calculated) from Total Ca/Mg	EC100A ALS Environmental - Waterloo	Water	APHA 2340B	"Hardness (as CaCO <sub>3</sub> ), from total Ca/Mg" is calculated from the sum of total Calcium and Magnesium concentrations, expressed in CaCO <sub>3</sub> equivalents. "Total Hardness" refers to the sum of Calcium and Magnesium Hardness. Hardness is normally or preferentially calculated from dissolved Calcium and Magnesium concentrations, because it is a property of water due to dissolved divalent cations. Hardness from total Ca/Mg is normally comparable to Dissolved Hardness in non-turbid waters.

Analytical Methods		Method / Lab	Matrix	Method Reference	Method Descriptions
Ion Balance using Total Metals		EC101A ALS Environmental - Waterloo	Water	APHA 1030E	Cation Sum (using total metals), Anion Sum, and Ion Balance are calculated based on guidance from APHA Standard Methods (1030E Checking Correctness of Analysis). Minor ions are included where data is present. Ion Balance cannot be calculated accurately for waters with very low electrical conductivity (EC).
Sodium Adsorption Ratio [SAR] from Total Metals		EC102 ALS Environmental - Waterloo	Water	CCME Sodium Adsorption Ratio (SAR)	The Sodium Adsorption Ratio (SAR) for a water sample is calculated from the Sodium, Calcium, and Magnesium concentrations of the water, using the same calculations as would be used for a sediment paste extract.
TDS calculated from conductivity		EC103A ALS Environmental - Waterloo	Water	APHA 1030 E	Total dissolved solids (as mg/L) can be estimated by multiplying electrical conductance (in umhos/cm) by 0.65.
Saturation Index using Laboratory pH (Ca-T)		EC105A ALS Environmental - Waterloo	Water	APHA 2330B	Langelier Index provides an indication of scale formation potential at a given pH and temperature, and is calculated as per APHA 2330B Saturation Index. Positive values indicate oversaturation with respect to CaCO <sub>3</sub> . Negative values indicate undersaturation of CaCO <sub>3</sub> . This calculation uses laboratory pH measurements and provides estimates of Langelier Index at temperatures of 4, 15, 20, 25, 66, and 77°C. Ryznar Stability Index is an alternative index used for scale formation and corrosion potential.
Nitrate and Nitrite (as N) (Calculation)		EC235.N+N ALS Environmental - Waterloo	Water	EPA 300.0	Nitrate and Nitrite (as N) is a calculated parameter. Nitrate and Nitrite (as N) = Nitrite (as N) + Nitrate (as N).
Total Silicon as Silica (Calculation)		EC420.SiO <sub>2</sub> ALS Environmental - Waterloo	Water	N/A	Total Silicon (as SiO <sub>2</sub> ) is a calculated parameter. Total Silicon (as SiO <sub>2</sub> mg/L) = 2.139 x Total Silicon (mg/L).
Preparation Methods					
Preparation for Ammonia		EP298 ALS Environmental - Waterloo	Water		Sample preparation for Preserved Nutrients Water Quality Analysis.

GC-471

Chain of Custody

WIC



www.alsglobal.com  
Contact and company name below will appear on the final report

Select Report Format:  PDF  EXCEL  EDD (DIGITAL)  
Merge QC/QCI Reports with COA  YES  NO  N/A  
 Compare Results to Criteria on Report - provide details below if box checked

Select Distribution:  EMAIL  MAIL  FAX  
Email 1 or Fax: jgerrits@cfcrozier.ca  
Email 2

Telephone: +1 519 886 6910  
DQ-101011-YY 11/11/2019 09:10 AM



Turnaround Time (TAT) Requested

Re: <input type="text" value="55 Wyndham St N #215"/>	City/Province: <input type="text" value="Guelph / ON"/>	Postal Code: <input type="text" value="N1H 7T8"/>	Invoice To: <input type="text" value="Same as Report To"/> <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	Copy of Invoice with Report <input type="checkbox"/>	Email 1 or Fax <input type="text" value="mhatt@cfcrozier.ca"/>	Email 2 <input type="checkbox"/>	Oil and Gas Required Fields (client use)	PO#	ROUTINE [R] if received by 3pm M-F - 20% rush surcharge min 4 day [P1] if received by 3pm M-F - 20% rush surcharge min 3 day [P3] if received by 3pm M-F - 25% rush surcharge min 2 day [P2] if received by 3pm M-F - 50% rush surcharge min 1 day [E] if received by 3pm M-F - 100% rush surcharge min Same day [E2] if received by 10am M-S - 200% rush surcharge min Additional fees may apply to rush requests on weekend
Company: <input type="text" value="ALS Client Code / QUOTE #: CFCR100 / 2024 SOA"/>	Contact: <input type="text" value="Job / Project #: 2457-6768"/>	Requisitioner: <input type="text" value="PO / AFE: LSD: ALS Sample # (ALS use only): W 12 2109348A"/>	Location: <input type="text" value="ALS Contact: Andrew Martin Sampler: (ALS use only) Sample 1 Sample 2"/>	Date <input type="text" value="18/04/24"/>	Time <input type="text" value="12:00"/>	Sample Type <input type="text" value="Drinking"/>	NUMBER OF CONTAINERS		
ROUTINE POTABILITY									
SAMPLING									
SAMPLE HOLD									
EXTRAS									
SUSPECTED HAZARD (see notes)									

For all tests with rush TATs requested, please contact your AM to confirm availability.

Analysis Request  
Indicate Filtered (F), Preserved (P) or Filtered and Preserved (F/P) below

CO-101011-YY 11/11/2019 09:10 AM

Re: 

Re: &lt;input type="text" value="55 Wyndham St N #21

# APPENDIX D

## Nitrate Impact Assessment Calculations



**Project Name:** 752-8 Petersen Road  
**Project Number:** 2497-6768  
**Date:** 2025-12-15  
**Designed By:** CM  
**Checked By:** CG

### D-5-4 IMPACT ASSESSMENT

#### Calculate the Nitrate Concentration at Property Boundary

Parameter	Value	Unit	Notes:
<b>Infiltation Volume</b>			
Area of Dilution =	5.19	ha	Area of site and surroundings.
Background Nitrate Quality in Groundwater =	0.00	mg/L	
Annual Infiltration Rate =	150	mm/m <sup>2</sup> /yr	Estimated annual infiltration rate based on MECP values
	4,109.59	L/ha/day	
Annual Infiltration Volume =	7,785	m <sup>3</sup> /year	
Total Average Background Nitrate =	0	mg/day	
<b>Sewage Effluent Volume</b>			
Proposed Number of Lots =	1		
Average Daily Volume of Sewage Effluent =	9,600	L/day	Maximum daily flow
Number of Days of Operation/Use =	365	days/year	
Annual Volume of Sewage Effluent =	3,504	m <sup>3</sup> /year	
Nitrate Concentration in wastewater =	40.0	mg/L	MECP standard effluent for conventional systems = 40 mg/L
Total Average Nitrate Loading =	384,000	mg/day	
<b>Totals</b>			
Total Dilutant = wastewater V + infiltration V =	11,289	m <sup>3</sup> /year	
Nitrate Concentration in Percolate =	12.42	mg/L	Less than 10 mg/L, sufficient for D-5-4 Impact Assessment



**Project Name:** 752-8 Petersen Road  
**Project Number:** 2497-6768  
**Date:** 2025-12-15  
**Designed By:** CM  
**Checked By:** CG

### D-5-4 IMPACT ASSESSMENT (with Nitrate Removal)


#### Calculate the Nitrate Concentration at Property Boundary

Parameter	Value	Unit	Notes:
<b>Infiltation Volume</b>			
Area of Dilution =	5.19	ha	Area of site and surroundings.
Background Nitrate Quality in Groundwater =	0.00	mg/L	
Annual Infiltration Rate =	150	mm/m <sup>2</sup> /yr	Estimated annual infiltration rate based on MECP values
	4,109.59	L/ha/day	
Annual Infiltration Volume =	7,785	m <sup>3</sup> /year	
Total Average Background Nitrate =	0	mg/day	
<b>Sewage Effluent Volume</b>			
Proposed Number of Lots =	1		
Average Daily Volume of Sewage Effluent =	9,600	L/day	Maximum daily flow
Number of Days of Operation/Use =	365	days/year	
Annual Volume of Sewage Effluent =	3,504	m <sup>3</sup> /year	
Nitrate Concentration in wastewater =	30.0	mg/L	Considering 25% nitrate removal
Total Average Nitrate Loading =	288,000	mg/day	
<b>Totals</b>			
Total Dilutant = wastewater V + infiltration V =	11,289	m <sup>3</sup> /year	
Nitrate Concentration in Percolate =	9.31	mg/L	Less than 10 mg/L, sufficient for D-5-4 Impact Assessment




## IMPACT ASSESSMENT

MOE, 2008




### Calculate the Nitrate Concentration at a Boundary (Property or Surface Water)

 = Manual Data Entry


#### Infiltration Volume

Area of Dilution =  5.19 ha  
Background Nitrate Quality in Groundwater =  0 mg/L  
Annual Infiltration Rate =  150 mm/m<sup>2</sup>/yr  
Annual Infiltration Volume =  7,785 m<sup>3</sup>

#### Sewage Effluent Volume

Average Daily Volume of Sewage Effluent =  6033.333 L/day (if residential, 1000 L/home/day)  
Number of Days of Operation/Use =  365 days/year  
Annual Volume of Sewage Effluent =  2,202 m<sup>3</sup>  
Maximum Nitrate Concentration at Boundary =  2.5 mg/L; use 2.5 for g/w, 3.0 for s/w

#### Totals

Total Dilutant = wastewater V + infiltration V =  9,987 m<sup>3</sup>/year  
Maximum Allowable Nitrate Concentration in Effluent  11.34 mg/L

# FIGURES



### Legend

Site Limits

#### Figure Notes:

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF C.F. CROZIER & ASSOCIATES INC. AND THE REPRODUCTION OF ANY PART OF IT WITHOUT PRIOR WRITTEN CONSENT OF THIS OFFICE IS STRICTLY PROHIBITED.

THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, LEVELS, AND DATUMS ON SITE AND REPORT ANY DISCREPANCIES OR OMISSIONS TO THIS OFFICE PRIOR TO CONSTRUCTION.

THIS DRAWING IS TO BE READ AND UNDERSTOOD IN CONJUNCTION WITH ALL OTHER PLANS AND DOCUMENTS APPLICABLE TO THIS PROJECT. DO NOT SCALE THIS DRAWING.

ALL EXISTING UNDERGROUND UTILITIES TO BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO CONSTRUCTION.

#### Project:

752 Peterson Road

#### Figure:


Site Location Plan



**CROZIER**  
CONSULTING ENGINEERS

Drawn:	Design:	Project No.
J.M	J.M	2497 - 6768
Date:	GCS:	Scale:
2024-05-27	NAD 1983	1:7,500

Fig. 1



## Legend

- Site Limits
- Physiography
- 53: Algonquin Highlands

Figure Notes:  
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF C.F. CROZIER & ASSOCIATES INC. AND THE REPRODUCTION OF ANY PART OF IT WITHOUT PRIOR WRITTEN CONSENT OF THIS OFFICE IS STRICTLY PROHIBITED.

THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, LEVELS, AND DATUMS ON SITE AND REPORT ANY DISCREPANCIES OR OMISSIONS TO THIS OFFICE PRIOR TO CONSTRUCTION.

THIS DRAWING IS TO BE READ AND UNDERSTOOD IN CONJUNCTION WITH ALL OTHER PLANS AND DOCUMENTS APPLICABLE TO THIS PROJECT. DO NOT SCALE THIS DRAWING.


ALL EXISTING UNDERGROUND UTILITIES TO BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO CONSTRUCTION.


Project:  
752 Peterson Road

Figure:  
Physiography



Drawn: J.M	Design: J.M	Project No. 2497 - 6768
Date: 2024-05-28	GCS: NAD 1983	Scale: 1:45,000







Williams Lake Rd

7421666

Peterson Rd

Burke Lake

Cannon Lake

7388986

2917533 2916314  
2917532

7433500  
2908373

2907831  
2921359

7160138

2918325

0 125 250 500 Metres



Key Plan: Site Location

1:115,000

### Legend

Site Limits

500m Site Buffer

MECP Well

Figure Notes:  
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF C.F. CROZIER & ASSOCIATES INC. AND THE REPRODUCTION OF ANY PART OF IT WITHOUT PRIOR WRITTEN CONSENT OF THIS OFFICE IS STRICTLY PROHIBITED.

THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS, LEVELS, AND DATUMS ON SITE AND REPORT ANY DISCREPANCIES OR OMISSIONS TO THIS OFFICE PRIOR TO CONSTRUCTION.

THIS DRAWING IS TO BE READ AND UNDERSTOOD IN CONJUNCTION WITH ALL OTHER PLANS AND DOCUMENTS APPLICABLE TO THIS PROJECT. DO NOT SCALE THIS DRAWING.

ALL EXISTING UNDERGROUND UTILITIES TO BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO CONSTRUCTION.

Project:  
752 Peterson Road

Figure:  
Well Location Plan



**CROZIER**  
CONSULTING ENGINEERS

Drawn:	J.M	Design:	J.M	Project No.	2497 - 6768
Date:	2025-06-27	GCS:	NAD 1983	Scale:	1:7,500

Fig. 5